

JICHUANGLIDE MX OIL

PREMIUM QUALITY CHAIN OIL WITH MOLY

PRODUCT DESCRIPTION:

JICHUANGLIDE MX is manufactured from a high quality medium VI solvent extracted naphthenic base oil fortified with molybdenum disulfide and a tackiness agent to impart maximum anti-wear and clinging characteristics.

TYPICAL USES:

- Recommended for lubrication of chains, rollers, and conveyors in industrial plants, contractors equipment, and agricultural equipment such as mechanical tomato and grape harvesters.
- Recommended for slow speed heavy loaded journal bearings, slides, ways, crossheads and sprockets.
- Chain saw bar and chain lubricant.

FEATURES:

- Economical - tackiness agent reduces oil consumption.
- Friction modifier (Moly) reduces wear.
- Tackiness agent reduces journal bearing end leakage.
- Reduces inventory - one oil for many uses.

TYPICAL INSPECTIONS

GRADE,ISO	68	100	150	220
GRAVITY,°API	23.7	24.1	23.8	24.7
FLASH POINT,°F.	440	450	465	485
FIRE POINT,°F.	485	495	505	535
POUR POINT,°F.	-10	-10	0	5
VISCOSITY:				
SUS@100°F.	340	527	798	1165
SUS@210°F.	52	59	69	95
cSt@40°C.	68	100	150	220
cSt@100°C.	7.6	9.6	12.5	18.6
COLOR,D-1500	grey	grey	grey	grey

VALUES SHOWN HERE ARE TYPICAL AND MAY VARY