



JICHUAN VI IMPROVER

PRODUCT DESCRIPTION:

JICHUAN VI IMPROVER has good shear stability for use in multi-grade crankcase oils, ATF, and industrial oils. Designed for new and old cars, trucks, tractors, motorcycles & boats, all motors and gear boxes. Keeps new cars like new longer, cleans and quiets hydraulic valves. Reduces noise in rear ends, gear & transercases for less friction, and reduces oil contamination, and carbon build up. Also used for reducing blow by sludge, varnish, oil dilution and pumping, and better results with smog control systems.

TYPICAL INSPECTIONS

SPECIFIC GRAVITY @ 60/60D F.	0.8595
DENSITY @ 60°F. LB/U.S. GAL.	7.16
FLASH POINT, (PM) °C./°F.	175/350
KINEMATIC VISCOSITY @ 40°C., cSt	8040
KINEMATIC VISCOSITY @ 100°C., cSt	811
COEFFICIENT OF THERMAL EXPANSION, VOL/VOL, °C./°F.	0.00077/0.00043
COLOR, ASTM D-1500	2.5
APPEARANCE	BRIGHT & CLEAR
CRC L-38 TEST 10 HOUR BREAKDOWN, %	22

VALUES SHOWN HERE ARE TYPICAL AND MAY VARY