

Shanghai JiChuan Trading

JiChuan Calsul Complex Grease

Product Description

JiChuan Calsul Complex Grease is a Calcium Sulfonate Complex thickened grease, formulated with a high viscosity base oil and special additives. JiChuan Calsul Complex Grease provides outstanding high temperature protection, excellent EP wear protection, water resistance and rust protection. And it is free of metal additives. JiChuan Calsul Complex Grease is widely used in steel mills, mining, paper industry, auto industry. Textile, manufacturing, agriculture and general purpose applications. radities y

Product Properties

- · Outstanding high temperature property and
- · Excellent EP wear protection
- Stable to ageing, liquifying and oxidation, Water resistance,
- · Excellent against corrosion, salt-water resistant

Fields of Application

JiChuan Calsul Complex Grease is mainly suitable for steel mills, mining, paper industry, auto industry. Textile, manufacturing, agriculture which need the high temperature, water and heavy-loaded conditions. For example, rolling mill bearing, food machinery contained moisture and acid gas, shovels, compactors, loaders, haul trucks, stenter bearings (plastic and textile industry), screw transmission shaft, kiln driving bearings, fan bearings, splined shafts etc.

Shanghai Jichuan Trading Co., Ltd.

Add: No 1201, Yinhai Building, Caoxi Road, Xuhui District, Shanghai

Tel: (86)021-64820099

24h Hotline: 15900706965 Fax: (86)021-64513829 Website: www.pingyiao.com E-mail: info@jichuan.sh.cn



Shanghai JiChuan Trading

Typical Data

JiChuan Calsul Complex Grease	2#	Test Method
Appearance	Smooth, Soft	Visual
Worked Penetration, 0.1mm	265 ~ 295	GB/T269
Dropping Point $^{\circ}$ C \geq	280	GB/T3498
Copper Corrosion (100℃,24h)	No change	GB/T7326
Worked Penetration 0.1mm Change, % 100,000 Strokes	20	GB/T269
Water Washout Losses (79°C,1h), % ≤	1.5	SH/T0109
Oxidation Stability (99°C,100h,0.770Mpa) PSI Drop, Mpa	0.070	SH/T0325
Base Oil Viscosity (-10°C,10S ⁻¹) Pa·S ≤	1000	SH/T0048
Vaperation (180°C,1h), % ≤	3	SH/T0337
Oil Separation (100℃,24h), % ≤	5	SH/T0324
$ \begin{array}{cccccccccccccccccccccccccccccccccccc$	1078 4900	SH/T0202

Available Package

JiChuan Calsul Complex Grease 800g Can

10Kg Pail 180Kg Drum

Shanghai Jichuan Trading Co.,Ltd.

Add: No 1201, Yinhai Building, Caoxi Road, Xuhui District, Shanghai

Tel: (86)021-64820099

24h Hotline: 15900706965 Fax: (86)021-64513829 Website: www.pingyiao.com E-mail: info@jichuan.sh.cn