



Shanghai Jichuan Trading

Schmierfix (Lubricant Fix)

DESCRIPTION

Lubricant Fix is a strongly adherent, high-performance grease for lubricating bearings, hinges and slide guides. Special additives allow high surface loading on slow-running transmissions.

PROPERTIES

- extremely adherent
- high EP properties
- water resistant
- resistant to commercially available water-based caustics
- compatible with all commercially available sealing materials
- stable to oxidation even during long periods of use
- reliable corrosion protection

Complies with the certification for grease in accordance with DIN 51 502

K1G-30

TECHNICAL DATA

Colour	: brown, natural colour	
Basis	: mineral oil	
Thickener	: metallic soap	
Drop point	: +140°C	
Working penetration	: 310-340	DIN 51 804
NLGI number	: 1	
Operating temperature range	: -30 °C to +100 °C	
EMCOR test	: 0 (no corrosion)	DIN 51 802
Water resistance at 90 °C	: 0	DIN 51 807

APPLICATION

For reliable lubrication of bearings, hinges and slide guides. Ideal areas of use: house, yard, garden, hobbies, garage and workshop. Lubricant Fix is also suitable for use as a special grease for lubricating ball bearings operating at high speeds, high temperatures and in corrosive atmospheres.

INSTRUCTIONS

Thoroughly clean surfaces removing dirt and old grease residues before application. Apply thinly to sliding surfaces and follow the instructions of the bearing and machine manufacturer.

AVAILABLE PACK SIZE

Lubricant Fix	50 g tube	Part no. 1080
	25 kg	Part no. 1081

Shanghai Jichuan Trading Co., Ltd.

Add: No 1201, Yinhai Building, Caoxi Road,
Xuhui District, Shanghai

24h Hotline: 15900706965

Website: www.pingyiao.com

Tel: (86) 021-64820099

Fax: (86) 021-64513829

E-mail: info@jichuan.sh.cn