



Shanghai Jichuan Trading

LM 49 Flow Paste

DESCRIPTION

LM 49 Flow Paste is an ideal assembly, lubricating and running-in paste. LM 49 Flow Paste is used for numerous applications in the manufacture, maintenance and servicing of motor vehicles, in agricultural applications, construction machines and industry. The product's very good adhesion and penetration properties ensure excellent lubrication and optimal wear reduction, even when sparingly used. Outstandingly easy to use and therefore specially suitable for the workshop.

PROPERTIES

- Spontaneously adherent
- Highest load-carrying capacity
- Good corrosion protection
- Universal use
- Quick and easy application
- Economical
- Emergency running properties

TECHNICAL DATA

Color : gray-black
Base : mineral oil
Additives (solid lubricants) : combination of synthetic solid lubricants
Consistency : thixotropic, fluid under shear
loading Density : 1.2 g/cm³
Operating temperature range : -30 °C to +600 °C

AREAS OF APPLICATION

LM 49 Flow Paste is ideal for use during assembly, repair and maintenance work on the entire motor vehicle. LM 49 Flow Paste also can be used in engineering and industrial applications.

APPLICATION

Apply thinly onto surfaces which must be clean but not free of oil. Does not need to be rubbed in. Can be applied to excess.

AVAILABLE PACK SIZES

LM 49 Flow Paste 500 g can with paint brush Part no. 3060

Shanghai Jichuan Trading Co.,Ltd.

Add: No 1201, Yin Hai Building, Caoxi Road,
Xuhui District, Shanghai

24h Hotline: 15900706965

Website: www.pingyiao.com

Tel: (86) 021-64820099

Fax: (86) 021-64513829

E-mail: info@jichuan.sh.cn