



Shanghai Jichuan Trading

LM 378 MoS₂ Grease

DESCRIPTION LM 378 MoS₂ Grease is a gel-thickened synthetic grease with molybdenumdisulphide for lubricating mechanically-loaded and wear-sensitive components at high and low temperatures.

PROPERTIES

- high pressure resistance
- good wear protection behaviour
- wide operating temperature range
- water resistant
- extreme resistance to ageing
- very compatible with plastics

Complies with the certification for grease in accordance with DIN 51502: KPFHC1N-40

TECHNICAL DATA

Basis	: synthetic oil/ inorganic thickeners	
Colour	: black	
NLGI	: 1	DIN 51818
Drop point	: non-drip	DIN ISO 2176
Working resistance after 60,000 double strokes	: max. + 30 1/10 mm	DIN ISO 2137
Operating temperature range	: -40 °C to +150 °C	
Water resistance	: 0 - 1	DIN 51807

APPLICATION LM 378 MoS₂ Grease is used for lubrication at high and low temperatures in fine mechanical products.

INSTRUCTIONS Before treating with LM 378 MoS₂ Grease, the contact surfaces must be clean and free from residues such as lubricants, dirt and moisture. Apply the product as a thin, uniform layer.

AVAILABLE PACK SIZE

LM 378 MoS₂ Grease 25 kg Part no. 3159

Shanghai Jichuan Trading Co.,Ltd.

Add: No 1201, Yin Hai Building, Caoxi Road, Tel: (86) 021-64820099
Xuhui District, Shanghai

24h Hotline: 15900706965

Fax: (86) 021-64513829

Website: www.pingyiao.com

E-mail: info@jichuan.sh.cn



Shanghai Jichuan Trading

Shanghai Jichuan Trading Co., Ltd.

Shanghai Jichuan Trading Co., Ltd.

Add: No 1201, Yinhai Building, Caoxi Road, Tel: (86) 021-64820099
Xuhui District, Shanghai

24h Hotline: 15900706965

Fax: (86) 021-64513829

Website: www.pingyiao.com

E-mail: info@jichuan.sh.cn