

## Shanghai Jichuan Trading

# GL 1 Getriebefließfett (GL 1 Transmission Flow Grease)

### **DESCRIPTION**

GL 1 Transmission Flow Grease is a strongly adherent, high-performance grease for lubricating bearings and closed and open drives. Due to the composition of GL 1, there is no separation of base oil or thickener due to delivery through long lubrication pipes, high pressure differences or steep shear gradients. Special additives allow high surface loading on slow-running transmissions.

## **PROPERTIES**

- extremely adherent
- high EP properties
- water resistant
- resistant to commercially available water-based caustics
- compatible with all commercially available sealing materials
- stable to oxidation even during long-term use
- reliable corrosion protection
- can be delivered by centralised lubrication systems
- does not contain solid lubricants

Complies with the certification for grease in accordance with DIN 51502 KP1K-30

TECHNICAL DATA

Colour : brown, natural colours

Basis : mineral oil
Thickener : metallic soap
Drop point : +140 °C

Worked penetration : 310 - 340 DIN 51 804

NLGI number : 1

Operating temperature range : -30 °C to +100 °C

EMCOR test : 0 (no corrosion) DIN 51 802

Resistance to oxidation : 0.5 at 100 h/100 °C

Water resistance at 90 °C : 0 DIN 51 807

### APPLICATION

Used in closed drives and in roller and plain bearings which are exposed to extreme conditions such as vibrations, shock or impact loading and eccentric bearings.

Shanghai Jichuan Trading Co.,Ltd.

Add: No 1201, Yinhai Building, Caoxi Road, Tel: (86) 021-64820099

Xuhui District, Shanghai

24h Hotline: 15900706965 Fax: (86) 021-64513829

Website: www.pingyiao.com E-mail: info@jichuan.sh.cn



# Shanghai Jichuan Trading

**INSTRUCTIONS** 

As usual for transmission flow greases, follow the instructions of the transmission and bearing manufacturers. Do not mix with other greases.

**AVAILABLE** 

Shanghai Jichuan Trading Co., Ltd.

thai lich No 1201, Yinhai Building, Caoxi Road, Tel: (86) 021-64820099

Xuhui District, Shanghai

24h Hotline: 15900706965 Fax: (86) 021-64513829

E-mail: info@jichuan.sh.cn Website: www.pingyiao.com