



Shanghai Jichuan Trading

LM 145 Schmierstoff-Compound (LM 145 Lubricant Compound)

DESCRIPTION Soft and extremely adherent lubricant for open drive elements. The film, which dries thoroughly, is especially suitable for open drives which are exposed to dust, water or the weather.

PROPERTIES

- extremely adherent
- protects against corrosion
- stable under extreme pressures
- stable to ageing and shear
- resistant to cold and hot water

TECHNICAL DATA

Colour : black
Basis : high-viscosity mineral oil
Solid lubricant : MoS₂
Operating temperature range : -30 °C to +110 °C
Water resistance at 90.C : 0 DIN 51 807

APPLICATION Used for all lubrication points which are directly exposed to environmental conditions. Lubrication of gearwheels, pivoted bogies or live rings, threaded spindles, chains, wire ropes, skids and bearings. Used for agricultural machinery, crane and conveyor plants and in shipping and transport companies.

INSTRUCTIONS Apply thinly to cleaned lubrication point. Lubrication intervals will be found in the operation instructions.
After use, clear spray nozzle by inverting the can and spraying until only the propellant emerges.

AVAILABLE PACK SIZE

LM 145 Lubricant compound 300 ml Part no. 4020

Shanghai Jichuan Trading Co.,Ltd.

Add : No 1201, Yin Hai Building, Caoxi Road, Xuhui District, Shanghai Tel: (86) 021-64820099

24h Hotline: 15900706965

Fax: (86) 021-64513829

Website: www.pingyiao.com

E-mail: info@jichuan.sh.cn



Shanghai Jichuan Trading

Shanghai Jichuan Trading Co., Ltd.

Shanghai Jichuan Trading Co., Ltd.

Add : No 1201, Yin Hai Building, Caoxi Road, Xuhui District, Shanghai

24h Hotline: 15900706965

Website: www.pingyiao.com

Fax: (86) 021-64513829

E-mail: info@jichuan.sh.cn