



# Shanghai Jichuan Trading

## LM 321 HT-Grease (LM 321 HT Grease)

### DESCRIPTION

LM 321 HT Grease is a synthetic high-temperature grease for long-life and permanent lubrication of roller and plain bearings which are subjected to high thermal loading.

### PROPERTIES

- extreme resistance to ageing
- wide operating temperature range
- good wear protection behaviour
- protects against corrosion
- high lubricating action
- especially recommended for high temperatures

Corresponds to and fulfils the following classifications and specifications:

KPFE2S-35      DIN 510502

### TECHNICAL DATA

Colour : pale, cream coloured  
Basis : synthetic oil  
Base oil viscosity +40 °C : 70 mm<sup>2</sup>/s  
Thickener : gel thickener  
Drop point : none  
NLGI number : 2  
Stability to liquifying P<sub>W10000</sub> : max. + 30°C  
EMCOR test : 0/1  
Operating temperature range: -35 °C to +210 °C  
short term +230 °C

删除的内容: G

删除的内容: Stability

删除的内容: liquifying

### APPLICATION

Used for blower and fan bearings, bearings in dryer plants in the textile and paper industry as well as stenter frame lubrication.

### INSTRUCTIONS

As usual for greases; do not mix with other greases.

### AVAILABLE PACK SIZE

LM 321 HT Grease	400 g	Part no. 4037
	1 kg	Part no. 4038

Shanghai Jichuan Trading Co.,Ltd.

Add: No 1201, Yin Hai Building, Caoxi Road, Tel: (86) 021-64820099

Xuhui District, Shanghai

24h Hotline: 15900706965

Fax: (86) 021-64513829

Website: www.pingyiao.com

E-mail: info@jichuan.sh.cn