

Shanghai Jichuan Trading

LM 41 MoS₂-Suspension (LM 41 MoS₂ Suspension)

DESCRIPTION

Colloidal MoS₂ solid lubricant suspension in mineral oil. This product is fully stabilised by special preparation methods and formulated for use in engines, hydraulic fluids, compressors and industrial transmissions.

PROPERTIES

- miscible with all commercially available engine oils
- stable under high thermal and dynamic loading
- no deposits and absolutely compatible with all commonly used filter systems
- reduces running-in and running wear
- improves high pressure loading capability
- guarantees limp-home properties
- reduces oil and fuel consumption
- increases the economy and operational reliability of units

TECHNICAL DATA

Colour : grey-black

Basis solvent raffinate

MoS₂ specifications complies with MIL-M7866 B, DEF 2304, CS 2819

MoS₂ particle size : majority < 0.3 μm

Solids content : 5 %

Operating temperature range: as with other mineral, MoS₂: above 400 °C

Density : 0.91 (0.92) g/cm³

 MoS_2 content : 4.5 %

Dynamic viscosity : approx. 300 mPa*s

APPLICATION

Added to the lubricating oils of engines, compressors, pumps, hydraulic plants and

industrial transmissions.

INSTRUCTIONS

Add 3-5 % to the lubricating oil. Additions up to 10 % possible under extreme load.

AVAILABLE

PACK SIZE LM 41 MoS₂ Suspension 1 ltr Part no. 4051

Shanghai Jichuan Trading Co.,Ltd.

Add: No 1201, Yinhai Building, Caoxi Road, Tel: (86) 021-64820099

Xuhui District, Shanghai

24h Hotline: 15900706965 Fax: (86) 021-64513829

Website: www.pingyiao.com E-mail: info@jichuan.sh.cn



Shanghai Jichuan Trading

ghai Jichuan "
No 12
Distr

No 1201, Yinhai Building, Caoxi Road, Tel: (86) 021-64820099

Xuhui District, Shanghai

24h Hotline: 15900706965 Fax: (86) 021-64513829

Website: www.pingyiao.com E-mail: info@jichuan.sh.cn