



Shanghai Jichuan Trading

Getriebefließfett GP0H-25 (Transmission Flow Grease GP0H-25)

DESCRIPTION

Liqui Moly Transmission Flow Grease GP0H-25 is a sodium soap transmission flow grease manufactured from carefully selected raw materials and special additives. The grease contains anti-wear additives and is characterized by its excellent corrosion protection properties. For use in closed transmissions for which grease lubrication has been specified.

Temperature range -25 °C to +100 °C
Short-term peak temperatures are permitted up to +120 °C.

Corresponds to and fulfills the following classifications and specifications:

Labeling according to	DIN 51502	GP0H-25
Lubricating grease	DIN 51826	GP0H-25

TECHNICAL DATA

Appearance and consistency	Natural color, semi-flowing and stretch properties		
Saponification type	Na		
Base oil			
Viscosity at 40 °C	DIN 51562	mm ² /s	220
Flash point	DIN ISO 2592	°C	240
Pour point	DIN ISO 3016	°C	-20
Dropping point	DIN ISO 2176	°C	150
Consistency grade	DIN 51818		0
Worked penetration	DIN ISO 2137	0.1 mm	360-380
Stability to liquifying	DIN ISO 2137		
Difference after 5,000 and 60 DH		0.1 mm	< 30
Difference after 100,000 and 60 DH		0.1 mm	< 40
Corrosion protection properties			
EMCOR method	DIN 51802	Corr. char.	0
Copper strip test	DIN 51811	Corr. char.	1-100
Solid foreign particles			
Test screen mesh 140 µ	DIN 51813	mg/kg	< 4
Water content	DIN ISO 3733	g/100 g	< 0.1
Ash, oxide	DIN EN 7	g/100 g	1.2

Shanghai Jichuan Trading Co., Ltd.

Add: No 1201, Yinhai Building, Caoxi Tel: (86) 021-64820099
Road, Xuhui District, Shanghai

24h Hotline: 15900706965

Fax: (86) 021-64513829

Website: www.pingyiao.com

E-mail: info@jichuan.sh.cn



Shanghai Jichuan Trading

Gear rig test, FZG method Method A/2.8/90	DIN 51354 Damage force class Spec. wt. change	mg/Kwh	12 < 0.27
Four-ball test/weld force	DIN 51350 Part 4	N	3000/3200

AVAILABLE PACK SIZE

Transmission Flow Grease GP0H-25	25 kg	Part no. 4199
	50 kg	Part no. 4200
	180 kg	Part no. 4201

Shanghai Jichuan Trading Co., Ltd.

Add: No 1201, Yinhai Building, Caoxi Road, Xuhui District, Shanghai

24h Hotline: 15900706965

Website: www.pingyiao.com

Fax: (86) 021-64513829

E-mail: info@jichuan.sh.cn