



Shanghai Jichuan Trading

Silentin 26

DESCRIPTION Silentin 26 is a gel-thickened synthetic grease with exceptional noise-damping properties.

PROPERTIES

- very effective noise-damper
- results in smooth running and smoother gear change
- very good resistance to ageing
- wide operating temperature range from approx. -40 °C to +120 °C
- low friction
- protection against wear and corrosion
- prevents stick-slip
- compatible with almost all plastics but limited compatibility with polymethylmethacrylate and polycarbonate.

TECHNICAL DATA

Colour	: bluish/greenish translucent grease	
Basis	: synthetic oil	
Operating temperature range	: approx. -40 °C to +120 °C	
NLGI number	: 0/00	DIN 51 818
Density at 20 °C	: 1.04 g/cm ³	DIN 51 757
Drop point	: non-drip	DIN ISO 2176
Flow pressure at -35 °C	: 500 hPa	
Copper corrosion	: 0 – 1	DIN 51 811
Oil separation 10d/40 °C	: max. 2.0 %	DIN 51 817
Water resistance	: 0 to 1 / 40 °C	DIN 51 807

APPLICATION Used for lubricating plastic friction pairs in office machinery, toys, domestic appliances, keyboards and optical and electronic equipment.

INSTRUCTIONS Apply thinly to the cleaned surfaces. Not compatible with all soap-based or mineral-based greases.

AVAILABLE PACK SIZE Silentin 26 1 kg Part no. 4232

Shanghai Jichuan Trading Co.,Ltd.

Add: No 1201, Yin Hai Building, Caoxi Road, Xuhui District, Shanghai

24h Hotline: 15900706965

Website: www.pingyiao.com

Tel: (86) 021-64820099

Fax: (86) 021-64513829

E-mail: info@jichuan.sh.cn



Shanghai Jichuan Trading

Shanghai Jichuan Trading Co., Ltd.

Shanghai Jichuan Trading Co.,Ltd.

Add: No 1201, Yin Hai Building, Caoxi Road, Xuhui District, Shanghai

24h Hotline: 15900706965

Website: www.pingyiao.com

Tel: (86) 021-64820099

Fax: (86) 021-64513829

E-mail: info@jichuan.sh.cn