

Shanghai Jichuan Trading

Flow Grease ZS KOOK-40

DESCRIPTION

Flow Grease ZS KOOK-40 is a lithium soap grease manufactured from carefully selected raw materials and special additives. The product is used for lubricating transmissions, gearwheel couplings and roller and plain bearings, under normal loading and for which flow grease is specified at low to medium speeds. It can also be used under dusty and damp operating conditions. Flow Grease ZS KOOK-40 is characterised by its high water resistance and adherence. additives for reducing wear and increasing load-carrying capacity. Recommended for HGV central lubrication systems.

Complies with the certification for grease in accordance with DIN 51 502 KOOK-40

TECHNICAL DATA

Colour : natural colours

Basis : mineral oil

Thickener : Li-12-hydroxystearate

 Drop point
 : 160 °C
 DIN ISO 2176

 NLGI number
 ::0
 DIN 51818

 penetration
 Worked: 420-440
 DIN 51804

temperature Operating

range : approx. -40 °C to +120

°C .

Water resistance at 90 °C : 1 DIN 51 807

INSTRUCTIONS

Use as usual for flow greases. The operating instructions of the transmission and bearing manufacturers must be followed.

Tel: (86) 021-64820099

AVAILABLE PACK SIZE

Flow Grease ZS KOOK-40

5 kg Part no. 4714 25 kg Part no. 4715 180 kg Part no. 4720

Shanghai Jichuan Trading Co.,Ltd.

Add: No 1201, Yinhai Building, Caoxi Road,

Xuhui District, Shanghai

24h Hotline: 15900706965 Fax: (86) 021-64513829

Website: www.pingyiao.com E-mail: info@jichuan.sh.cn



Shanghai Jichuan Trading

hanghai 'di

Shanghai Jichuan Trading Co.,Ltd.

Add: No 1201, Yinhai Building, Caoxi Road,

Xuhui District, Shanghai

24h Hotline: 15900706965

Website: www.pingyiao.com

Tel: (86) 021-64820099

Fax: (86) 021-64513829

E-mail: info@jichuan.sh.cn