



Shanghai Jichuan Trading

Weies Synth. HT-Fett (White Synth. HT Grease)

DESCRIPTION

White Synth. HT Grease is an outstanding lubricant for reducing friction and wear, especially at high temperatures and loads. The sealing properties of this product, its capacity to protect against corrosion and its high serviceability guarantee reliable lubrication.

PROPERTIES

- excellent temperature-consistency behaviour
- high load-carrying capacity
- stable to ageing
- high resistance to aggressive media
- water resistant
- can be delivered via centralised lubrication systems

Complies with the certification for grease in accordance with DIN 51502 KHC1/2S-30

TECHNICAL DATA

Colour	: white		
Basis	: synthetic oil		
Thickener	: org. polymers		
Base-oil viscosity at 40 °C	: approx. 410 mm ² /s	DIN	51562
Drop point	: > 240 °C	DIN ISO	2176
Worked penetration	: 287-317	DIN ISO	2137
NLGI number	: 1/2	DIN	51818
Operating temperature range	: from -30 °C -200 °C short term +230 °C		
Water resistance at 90 °C	: 0	DIN	51807
EMCOR test	: 0/0	DIN	51807

APPLICATION

Used for longlife lubrication of roller and plain bearings. Bearings on furnace systems exposed to high temperatures such as annealing furnaces and drying ovens, rotary tubular kilns, hot blast-air fans, especially electric motors, conveyor plants, hardening shops and paint shops.

Shanghai Jichuan Trading Co.,Ltd.

Add: No 1201, Yin Hai Building, Caoxi Road, Xuhui District, Shanghai

24h Hotline: 15900706965

Website: www.pingyiao.com

Tel: (86) 021-64820099

Fax: (86) 021-64513829

E-mail: info@jichuan.sh.cn



Shanghai Jichuan Trading

INSTRUCTIONS

As usual for grease. The operating instructions of the bearing manufacturers must be followed. Do not mix with other greases.

AVAILABLE PACK SIZE

White Synth. HT Grease

400 g cartridge

Part no. 8922

Shanghai Jichuan Trading Co., Ltd.

Shanghai Jichuan Trading Co.,Ltd.

Add: No 1201, Yinhai Building, Caoxi Road, Xuhui District, Shanghai

24h Hotline: 15900706965

Website: www.pingyiao.com

Tel: (86) 021-64820099

Fax: (86) 021-64513829

E-mail: info@jichuan.sh.cn