



# Shanghai Jichuan Trading

## LM 373 N Contact-Grease (LM 373 N Contact Grease)

### DESCRIPTION

LM 373 N Contact Grease is a grease-type, fully synthetic contact treatment preparation which is compatible with plastics and free of silicones. The special additives, synthetic oil and consistency modifiers in this product ensure that it can be used over a wide range of temperatures. The product shows no signs of chemical decomposition or resinifying even after long periods of use.

### PROPERTIES

- high resistance to ageing
- the synthetic base oil has excellent viscosity/temperature properties
- very good low and high temperature properties
- outstanding wear protection
- low friction
- protection against corrosion and oxidation
- water resistant
- silicone-free

### TECHNICAL DATA

Colour	: natural colours		
Basis	: synthetic oil		
consistency modifiers	: inorganic thickeners		
Density at 20 °C	: 0.9	g/ml	DIN 51 757
Flow pressure at -35°C	: 450	hPa	DIN 51 805
Drop point	: non-drip		DIN ISO 2176
NLGI number	: 1		DIN 51 804
Operating temperature range:	-40 °C to +150 °C		
Oil separation	: < 10	wt %	DIN 51 817
Water resistance	: 0 - 1		DIN 51 807
Copper corrosion	: 0		DIN 51 811
Specific electrical resistance	: 2.4 • 10 <sup>7</sup>	Ohm • cm	

### APPLICATION

LM 373 N Contact Grease is used for lubricating and treating the mechanical and electrical components in switches. LM 373 N Contact Grease is also used for fine mechanical products. The product can be used over a wide range of temperatures, is very compatible with plastics and is extremely stable to ageing.

Shanghai Jichuan Trading Co.,Ltd.

Add: No 1201, Yinhai Building, Caoxi Road, Tel: (86) 021-64820099  
Xuhui District, Shanghai

24h Hotline: 15900706965

Fax: (86) 021-64513829

Website: [www.pingyiao.com](http://www.pingyiao.com)

E-mail: [info@jichuan.sh.cn](mailto:info@jichuan.sh.cn)



# Shanghai Jichuan Trading

## INSTRUCTIONS

Before treating with LM 373 N Contact Grease, the contact surfaces must be clean and free from residues such as lubricants, dirt and moisture. Apply the product as a thin, uniform layer.

## AVAILABLE PACK SIZE

LM 373 N Contact Grease	500 g	can	Part no. 3151
LM 373 N Contact Grease	5 kg	tub	Part no. 3153
LM 373 N Contact Grease	25 kg	hobbock	Part no. 3150

Shanghai Jichuan Trading Co.,Ltd.

Add: No 1201, Yinhai Building, Caoxi Road, Xuhui District, Shanghai

24h Hotline: 15900706965

Website: [www.pingyiao.com](http://www.pingyiao.com)

Fax: (86) 021-64513829

E-mail: [info@jichuan.sh.cn](mailto:info@jichuan.sh.cn)