



Shanghai Jichuan Trading

LM 369 Contact-Grease

DESCRIPTION

LM 369 Contact Grease is a gel-thickened, silicone-free synthetic grease which has been formulated for universal use. It is particularly suitable for fine mechanical lubrication points. For lubrication and care of electrical contacts and guideways.

PROPERTIES

- high resistance to ageing
- the synthetic base oil has excellent viscosity/temperature properties
- very good low and high temperature properties
- protection against corrosion and oxidation
- water resistant
- silicone-free

TECHNICAL DATA

Colour	: yellow		
Basis	: synthetic oil		
Consistency modifiers	: inorganic thickeners		
Density at 20 °C	: 0.9	g/cm ³	DIN 51 757
Flow pressure at -35 °C	: 450	hPa	DIN 51 805
Drop point	: non-drip		DIN ISO 2176
NLGI number	: 1 - 2		DIN ISO 2137
Operating temperature range:	-45 °C to +150 °C		
Oil separation, 10d/40 °C	: max. 3	wt %	DIN 51 817
Water resistance	: 0 - 1		DIN 51 807
Working resistance after 60,000 double strokes	: max. +30	1/10 mm	DIN ISO 2137
Copper corrosion	: 0		DIN 51 811
Specific electrical resistance	: 3.1 • 10 ⁷	Ohm • cm	

APPLICATION

Contact grease for universal use with wide operating temperature range under high loading.

INSTRUCTIONS

Before treating with LM 369 Contact Grease, the contact surfaces must be clean and free from residues such as lubricants, dirt and moisture. Apply the product as a thin, uniform layer.

Shanghai Jichuan Trading Co.,Ltd.

Add: No 1201, Yin Hai Building, Caoxi Road, Xuhui District, Shanghai

24h Hotline: 15900706965

Website: www.pingyiao.com

Fax: (86) 021-64513829

E-mail: info@jichuan.sh.cn



Shanghai Jichuan Trading

Before using the product, check for compatibility plastics at risk from stress-cracking.

**AVAILABLE
PACK SIZE**

LM 369 Contact Grease
LM 369 Contact Grease

500 g can
25 kg hobbock

Part no. 3176
Part no. 3184

Shanghai Jichuan Trading Co.,Ltd.

Add: No 1201, Yin Hai Building, Caoxi Road, Xuhui District, Shanghai

24h Hotline: 15900706965

Website: www.pingyiao.com

Fax: (86) 021-64513829

E-mail: info@jichuan.sh.cn