

PTFE-Pulver-Spray (PTFE Powder Spray)

(PIFE PO	waei	r Spra	y)		× Or		
(Teflon or polytetrafluore has universal application	ethylene). \ n particular	With its long ly in work a	-term reas w	lubricating a /here oil or s	ction, this product ilicone-based		
 no taste high chemical resistance high heat resistance low friction eliminates squeaks 	ce	nsulation	j.	ç.			
	· ·	4					
Basis: Density at 20°C Operating temperature r Propellant: PTFE Powder Spray is a automotive engineering, rails such as those found	a lubricant it is the op d under se	-40 °C to + propane/bu which can b btimum lubri ats. It can a	250 °C utane e use cant fo lso be	d on practica or belt mech used as a lu	anisms and guide Jbricant and		
rails, rollers, chains and	threads. It	also has ur	niversa	al application			
Spray PTFE Powder Spray thinly and uniformly onto the clean and grease-free surface. If greater layer thickness is required, the preceding coat must be allowed to dry before applying another coat. After use, clear spray nozzle by inverting can and spraying until only the propellant emerges.							
PTFE Powder Spray		400) ml	Aerosol	Art.Nr. 3076		
ding Co.,Ltd.							
nai Building, Caoxi	Tel: (86	5) 021-6482	20099				
			Fax: (86) 021-64513829				
	(PTFE Powder Spray is a (Teflon or polytetrafluored has universal application agents cannot be used b of other reasons. - easy to use - free of oil, grease and s - no taste - high chemical resistance - low friction - eliminates squeaks - suitable for care, protect Colour: Basis: Density at 20°C Operating temperature r Propellant: PTFE Powder Spray is a automotive engineering, rails such as those found separating agent for elimin in industry it is used part rails, rollers, chains and Ideally suitable as a rele Spray PTFE Powder Spray is a automotive engineering, rails cuch as those found separating agent for elimin n industry it is used part rails, rollers, chains and Ideally suitable as a rele Spray PTFE Powder Spray is urface. If greater layer for a for use, clear spray no propellant emerges. PTFE Powder Spray	<pre>(PTFE Powder Spray is a grease-fr (Teflon or polytetrafluorethylene). V has universal application particular agents cannot be used because the of other reasons.</pre> - easy to use - ree of oil, grease and silicones - no taste - high chemical resistance - high heat resistance - low friction - eliminates squeaks - suitable for care, protection and it Colour: Basis: Density at 20°C Operating temperature range: Propellant: PTFE Powder Spray is a lubricant automotive engineering, it is the op rails such as those found under se separating agent for eliminating an In industry it is used particularly in rails, rollers, chains and threads. It Ideally suitable as a release agent Spray PTFE Powder Spray thinly a surface. If greater layer thickness if ay before applying another coat. After use, clear spray nozzle by inv propellant emerges. PTFE Powder Spray ding Co.,Ltd. nai Building, Caoxi Tel: (86 Shanghai 06965 Fax: (84)	PTFE Powder Spray is a grease-free lubricant (Teflon or polytetrafluorethylene). With its long has universal application particularly in work a agents cannot be used because they ruin finis of other reasons. - easy to use - free of oil, grease and silicones - no taste - high chemical resistance - high neat resistance - low friction - eliminates squeaks - suitable for care, protection and insulation Colour: white Basis: PTFE Density at 20°C 0.58 g/cm ³ Operating temperature range: -40 °C to + Propellant: propane/bu PTFE Powder Spray is a lubricant which can b automotive engineering, it is the optimum lubri rails such as those found under seats. It can a separating agent for eliminating any type of no In industry it is used particularly in processing rails, rollers, chains and threads. It also has ur Ideally suitable as a release agent in plastics p Spray PTFE Powder Spray thinly and uniform surface. If greater layer thickness is required, to dry before applying another coat. After use, clear spray nozzle by inverting can a propellant emerges. PTFE Powder Spray 400 ding Co.,Ltd. nai Building, Caoxi Tel: (86) 021-6482 Shanghai 06965 Fax: (86) 021-645	(PTFE Powder Spray is a grease-free lubricant and re (Teflon or polytetrafluorethylene). With its long-term has universal application particularly in work areas wagents cannot be used because they ruin finishing word other reasons. - easy to use - free of oil, grease and silicones - no taste - high chemical resistance - high chemical resistance - high neat resistance - low friction - eliminates squeaks - suitable for care, protection and insulation Colour: white Basis: PTFE Density at 20°C 0.58 g/cm³ Operating temperature range: -40 °C to +250 °C Propellant: propane/butane PTFE Powder Spray is a lubricant which can be user automotive engineering, it is the optimum lubricant for rails such as those found under seats. It can also be separating agent for eliminating any type of noise for in industry it is used particularly in processing textilerails, rollers, chains and threads. It also has universatioeally suitable as a release agent in plastics proces Spray PTFE Powder Spray mozzle by inverting can and sp propellant emerges. PTFE Powder Spray 400 ml ding Co.,Ltd. nai Building, Caoxi Tel: (86) 021-648200099 Shanghai 02965 Fax: (86) 021-64513829	(PTFE Powder Spray is a grease-free lubricant and release agen (Teflon or polytetrafluorethylene). With its long-term lubricating a has universal application particularly in work areas where oil or s agents cannot be used because they ruin finishing work such as of other reasons. - easy to use - free of oil, grease and silicones - no taste - high chemical resistance - low friction - eliminates squeaks - suitable for care, protection and insulation Colour: white Basis: Density at 20°C 0.58 g/cm³ Operating temperature range: -40 °C to +250 °C Propellant: propane/butane PTFE Powder Spray is a lubricant which can be used on practica automotive engineering, it is the optimum lubricant for belt mech rails such as those found under seats. It can also be used as a the separating agent for eliminating any type of noise from covers ar in industry it is used particularly in processing textiles and wood rails, rollers, chains and threads. It also has universal application ideally suitable as a release agent in plastics processing. Spray PTFE Powder Spray thinly and uniformly onto the clean an surface. If greater layer thickness is required, the preceding coat dry before applying another coat. After use, clear spray nozzle by inverting can and spraying until propellant emerges. PTFE Powder Spray 400 ml Aerosol ding Co.,Ltd. ai Building, Caoxi Tel: (86) 021-64820099 Shanghai		



Shanghai Jichuan Trading

Shanghai Jichuan Trading Co.,Ltd. Add: No 1201, Yinhai Building, Caoxi Road, Xuhui District, Shanghai 24h Hotline: 15900706965 Website: www.pingyiao.com

Tel: (86) 021-64820099

tichuan tradine

Fax: (86) 021-64513829 E-mail: info@jichuan.sh.cn