



Shanghai Jichuan Trading

Universalöl für Lebensmitteltechnik (Universal Oil for Food Technology)

DESCRIPTION Medically pure, multi-purpose oil in accordance with the German Pharmacopoeia DAB 10 with excellent penetration properties.

PROPERTIES

- free of taste and smell
- safe to use
- does not attack plastics
- inhibits corrosion
- does not contain resins or acids
- high purity

TECHNICAL DATA

ISO Viscosity class	VG 15		DIN 51519
Viscosity at 40 °C	16.3	mm ² /s	DIN 51562
Viscosity at 20 °C	40	mm ² /s	DIN 51562
Colour:	water white		
Density at 15 °C	0.862	g/cm ³	DIN 51757
Flash point:	166	°C	DIN ISO 2592
Pour point	-24	°C	DIN ISO 3016
Ash, Oxide	< 0.001	g/100 g	DIN EN 7
Asphalt content	n.f.	g/100 g	DIN 51595
Insolubles content	n.f.	g/100 g	DIN 51592
Water content	n.f.	g/100 g	DIN ISO 3733
Neutralisation number, (acid value)	0.01	mg KOH/g	DIN 51558 Teil 1

* n.f. = none found

APPLICATION Use for lubrication and maintenance of components such as bearings, needles and chains etc, in the pharmaceutical, cosmetics and medical industry as well as agriculture and the food industry.

INSTRUCTIONS Before treating with Universal Oil, all components must be clean and free of residues. Apply a thin uniform coat.

AVAILABLE PACK SIZE Universal Oil 100 ml atomiser Part no. 3121

Shanghai Jichuan Trading Co.,Ltd.

Add: No 1201, Yin Hai Building, Caoxi Road, Xuhui District, Shanghai

24h Hotline: 15900706965

Fax: (86) 021-64513829

Website: www.pingyiao.com

E-mail: info@jichuan.sh.cn



Shanghai Jichuan Trading

Shanghai Jichuan Trading Co., Ltd.

Shanghai Jichuan Trading Co., Ltd.

Add: No 1201, Yinhai Building, Caoxi Road, Xuhui District, Shanghai

24h Hotline: 15900706965

Website: www.pingyiao.com

Fax: (86) 021-64513829

E-mail: info@jichuan.sh.cn