

Shanghai Jichuan Trading

LM 48 Sprühpaste (LM 48 Spray Paste)

DESCRIPTION

Sprayable mineral oil-based MoS₂ assembly paste containing lubricants. Due to a special preparation process, this paste is suitable for the highest requirements.

PROPERTIES

- easy to use

- reliable wear protection - good corrosion protection

- universal use

- outstandingly adherent

- low friction

- limp-home lubrication

TECHNICAL DATA

Colour grey-black Basis mineral oil

Additives (solid lubricants) MoS₂ 33 %, graphite 6 %

Propellant

propane/butane Operating temperature range : -30 °C to +450 °C 0.12 µ/no rattle

Pressfit-Test Screw test thread friction : 0.09 µ at room temperature

APPLICATION

Assembly, repair and maintenance in all areas of engineering. For basic lubrication and preventing running-in damage. "For-life" lubrication of bearings, joints and small components. Specially suitable for surfaces and components with complex shapes.

INSTRUCTIONS

Shake spray can vigorously before use. Spray the product thinly and uniformly onto clean surfaces. Avoid excess for economical reasons. After use, clear the nozzle by spraying with the can inverted.

AVAILABLE

PACK SIZE LM 48 Assembly Paste Part No. 3045 300 ml 500 ml Part No. 4057

Shanghai Jichuan Trading Co.,Ltd.

No 1201, Yinhai Building, Caoxi Road, Tel: (86) 021-64820099

Xuhui District, Shanghai

24h Hotline: 15900706965 Fax: (86) 021-64513829

Website: www.pingyiao.com E-mail: info@jichuan.sh.cn



Shanghai Jichuan Trading

ghai Jichuan "
No 12
Distr

No 1201, Yinhai Building, Caoxi Road, Tel: (86) 021-64820099

Xuhui District, Shanghai

24h Hotline: 15900706965 Fax: (86) 021-64513829

Website: www.pingyiao.com E-mail: info@jichuan.sh.cn