



Shanghai Jichuan Trading

Zink-Spray (Zinc Spray)

DESCRIPTION Zinc Spray is an active means of cathodic corrosion protection. The resistant, flexible, heat-resistant zinc film produced protects iron and steel components from rust and corrosion.

- PROPERTIES**
- lasting corrosion protection
 - smooth, pore-free film
 - high zinc content
 - electrically conductive
 - quick drying and can be painted over
 - high heat resistance
 - spot weldable

**TECHNICAL
DATA**

Colour : matt grey
Zinc purity : > 99 %
Proportion of zinc : > 99 % (as a dry film)
Binder : special resins
Temperature range : up to 500 °C
Density : 1.95 g/cm³
Drying time : 5-7 min. dust dry
20-30 min. touch dry
can be painted over after 8 hours
Propellant : propane/butane

APPLICATION Protects iron and steel components from rust and corrosion. For repairing damaged galvanised surfaces. Base coat for and protection of vehicle-body components and exhaust systems.

INSTRUCTIONS Shake can until the steel balls work free. Spray onto clean and degreased metallic surfaces. Can be painted over after 8 hours.
Layer thickness of the zinc film dry after a single spraying: 25-35 µm

After use, clear spray nozzle by inverting can and spraying until only the propellant emerges.

**AVAILABLE
PACK SIZE**

Zinc Spray 400 ml Aerosol, Part no. 1540

Shanghai Jichuan Trading Co.,Ltd.

Add: No 1201, Yin Hai Building, Caoxi Road,
Xuhui District, Shanghai

24h Hotline: 15900706965

Website: www.pingyiao.com

Tel: (86) 021-64820099

Fax: (86) 021-64513829

E-mail: info@jichuan.sh.cn



Shanghai Jichuan Trading

Shanghai Jichuan Trading Co., Ltd.

Shanghai Jichuan Trading Co., Ltd.

Add: No 1201, Yin Hai Building, Caoxi Road,
Xuhui District, Shanghai

24h Hotline: 15900706965

Website: www.pingyiao.com

Tel: (86) 021-64820099

Fax: (86) 021-64513829

E-mail: info@jichuan.sh.cn