Glanz-Zink-Spray
(Bright Zinc Spray)

DESCRIPTION

Bright Zinc Spray is an active means of cathodic corrosion protection. The resistant, flexible, heat-resistant zinc film which is produced protects iron and steel components from rust and corrosion. Bright Zinc Spray can also be used as the only means of corrosion protection.

PROPERTIES

- lasting corrosion protection
- smooth, pore-free film
- high zinc content
- electrically conductive
- quick drying and can be painted over
- high heat resistance
- spot weldable

TECHNICAL DATA

Colour	: grey, bright
Zinc purity	: > 99 %
Proportion of zinc	: > 99 % (as a dry film)
Binder	: special resins
Temperature range	: up to 490 °C
Density	: 1.95 g/cm³
Drying time	: 5-7 min. dust dry
	20-30 min. touch dry
	can be painted over after 8 hours
Propellant	: propane/butane

APPLICATION

Used to protect iron and steel components from rust and corrosion. Suitable for repairing all damaged forms of galvanising (hot-dip, flame spraying and electroplated zinc). Bright Zinc Spray can also be used as the only means of weather-resistant corrosion protection.

INSTRUCTIONS

Shake can vigorously for at least 1 minute before use. Spray onto clean, dry, degreased metallic surfaces. Can be painted over after 8 hours.
Layer thickness of the zinc film dry after a single spraying: 25-35 µm.

After use, clear spray nozzle by inverting can and spraying until only the propellant emerges.

AVAILABLE PACK SIZE

Bright Zinc Spray   400 ml   Aerosol,   Part no. 1640

Shanghai Jichuan Trading Co.,Ltd.

Add： No 1201, Yinhai Building, Caoxi Road, Xuhui District, Shanghai

Tel：(86) 021-64820099

24h Hotline：15900706965

Fax：(86) 021-64513829

Website：www.pingyiao.com

E-mail：info@jichuan.sh.cn

Shanghai Jichuan Trading Co.,Ltd.

Add：　No 1201, Yinhai Building, Caoxi Road,　　Tel：(86) 021-64820099
Xuhui District, Shanghai

24h Hotline：15900706965　　　　　　　　Fax：(86) 021-64513829

Website：www.pingyiao.com　　　　　　　　E-mail：info@jichuan.sh.cn