



Shanghai Jichuan Trading

Schrauben-Sicherung hochfest (Threadlock high strength)

DESCRIPTION Threadlock high strength is the optimum thread-locking adhesive. This product can be used on oily surfaces and galvanised screws.

PROPERTIES

- resists loosening due to vibration
- wide operating temperature range
- fast and reliable hardening
- controlled torque/stress ratio
- can be used on oily surfaces
- seals threads and prevents leaks

**TECHNICAL
DATA**

Basis : dimethacrylate ester
Start of polymerisation : 10-15 min.
Temperature range : -60 °C - +150 °C
Breakaway torque : 28-56 Nm
Compressed shear strength : 25 N/mm²
Final strength, steel : 8 hours
Final strength, non-ferrous
metals : 6-8 hours
Viscosity : 500 mPa.s
Screw size : M 10
Storage life : 2 years

APPLICATION Used for all commonly used screw and nut sizes and all grades.

INSTRUCTIONS Apply the product uniformly to screws and nuts. The paste cures in the absence of air.

**AVAILABLE
PACK SIZE**

Threadlock		
high strength	10 g tube	Part no. 3803
	50 g tube	Part no. 3804

Shanghai Jichuan Trading Co.,Ltd.

Add: No 1201, Yin Hai Building, Caoxi Road,
Xuhui District, Shanghai

24h Hotline: 15900706965

Website: www.pingyiao.com

Tel: (86) 021-64820099

Fax: (86) 021-64513829

E-mail: info@jichuan.sh.cn



Shanghai Jichuan Trading

Shanghai Jichuan Trading Co., Ltd.

Shanghai Jichuan Trading Co., Ltd.

Add: No 1201, Yinhai Building, Caoxi Road,
Xuhui District, Shanghai

24h Hotline: 15900706965

Website: www.pingyiao.com

Tel: (86) 021-64820099

Fax: (86) 021-64513829

E-mail: info@jichuan.sh.cn