

Shanghai Jichuan Trading

, Z.

Bush and Bearing Adhesive

DESCRIPTION		a high-strength, low-viscosity, oil-resistant, dhesive which does not contain solvents and cu	res in
PROPERTIES	 cures fast resistant to engine oil at 125 ° resistant to petrol and brake f very high strength even on sli low viscosity with excellent ca cures in the absence of oxyge 	luid at room temperature as well as to other mat ghtly oily surfaces apillary action	erials
TECHNICAL		. c ° O °	
DATA	Basis : c Storage life : a	green dimethylacrylate ester at least 2 years (unopened) nand strength 1-7 minutes function strength 1-2 hours final strength 6 hours	
	Strength class : H	87 N/mm² nigh strength - 55°C to + 175°C for a short time up to 220°C	
		pearings and suitable for bonding coaxial joints s d hubs as well as bonding plastics or rubber/met	
INSTRUCTIONS	films, dirt, paint or other coating	must be roughly freed from contaminants such a g materials to obtain the optimum bond. Wet the adhesive and then bring them together.	
AVAILABLE PACK SIZE	Bush and Bearing Adhesive	10 g plastic bottle Part no. 3806 50 g plastic bottle Part no. 3807	
Shanghai Jichuan Trac	ling Co. I td		
Add: No 1201, Yinhai Building, Caoxi Road, Xuhui District, Shanghai		Tel: (86) 021-64820099	
24h Hotline: 15900706965		Fax: (86) 021-64513829	
Website: www.pingyiao.com		E-mail: info@jichuan.sh.cn	
website: www.piligy	140.00111	L-man; mo@jienuali.sii.en	

Shanghai Jichuan Trading

tichuan

Shanghai Jichuan Trading Co.,Ltd.
Add: No 1201, Yinhai Building, Caoxi Road,
Xuhui District, Shanghai
24h Hotline: 15900706965
Website: www.pingyiao.com

anonai

Tel: (86) 021-64820099

Fax: (86) 021-64513829 E-mail: info@jichuan.sh.cn