



Shanghai Jichuan Trading

Flächendichtung (Surface Sealant)

DESCRIPTION

Surface Sealant is a single-component, medium-strength, high-viscosity, dimethylacrylate ester-based sealant which does not contain solvents and cures in the absence of oxygen.

PROPERTIES

- slow curing
- resistant to stresses and vibration
- medium strength
- also adheres to vertical surfaces
- cures in the absence of oxygen

TECHNICAL DATA

Colour : blue
Basis : dimethylacrylate ester
Storage life : at least 2 years (unopened)
Cure time at room temp. : hand strength 5-15 minutes
function strength 2-4 hours
final strength 10 hours
Compressed shear strength : 17 N/mm²
Strength class : medium strength
Operating temperature range: -60 °C to +150 °C

APPLICATION

Surface Sealant is suitable for sealing flanges, housings and covers. Suitable for joint sealing gaps from 0.1 to 0.5 mm.

INSTRUCTIONS

The components to be sealed must be free from contaminants such as oil films, dirt, paint or other coating materials. The optimum seal is achieved by roughening the surfaces.

AVAILABLE PACK SIZE

Surface Sealant

50 g plastic bottle

Part no. 3810

Shanghai Jichuan Trading Co., Ltd.

Add: No 1201, Yinhai Building, Caoxi Road,
Xuhui District, Shanghai

24h Hotline: 15900706965

Website: www.pingyiao.com

Tel: (86) 021-64820099

Fax: (86) 021-64513829

E-mail: info@jichuan.sh.cn



Shanghai Jichuan Trading

Shanghai Jichuan Trading Co., Ltd.

Shanghai Jichuan Trading Co., Ltd.

Add: No 1201, Yinhai Building, Caoxi Road,
Xuhui District, Shanghai

24h Hotline: 15900706965

Website: www.pingyiao.com

Tel: (86) 021-64820099

Fax: (86) 021-64513829

E-mail: info@jichuan.sh.cn