



Shanghai Jichuan Trading

Schrauben-Sicherung Feinmechanik (Threadlock Fine Mechanism)

DESCRIPTION

Threadlock Fine Mechanism is the optimum thread-locking adhesive. This product can be used on oily surfaces and galvanised screws.

PROPERTIES

- resists loosening due to vibration
- wide operating temperature range
- fast and reliable hardening
- controlled torque/stress ratio
- can be used on oily surfaces
- seals threads and prevents leaks

TECHNICAL DATA

Basis	: dimethacrylate ester
Start of polymerisation	: 2-10 min.
Temperature range	: -60 °C to +150 °C
Breakaway torque	: 17 Nm
Compressed shear strength	: 15 N/mm ²
Final strength, steel	: 12 hours
Final strength, non-ferrous metals	: 8 hours
Viscosity	: 500 mPa.s
Thread sizes	: up to M 10
Storage life	: 2 years

APPLICATION

Used for all commonly used screw and nut sizes and all grades.

INSTRUCTIONS

Apply the product uniformly to screws and nuts. The paste cures in the absence of air.

AVAILABLE PACK SIZE

Threadlock Fine Mechanism	10 g	Part no. 3812
------------------------------	------	---------------

Shanghai Jichuan Trading Co.,Ltd.

Add: No 1201, Yin Hai Building, Caoxi Road,
Xuhui District, Shanghai

24h Hotline: 15900706965

Website: www.pingyiao.com

Tel: (86) 021-64820099

Fax: (86) 021-64513829

E-mail: info@jichuan.sh.cn



Shanghai Jichuan Trading

Shanghai Jichuan Trading Co., Ltd.

Shanghai Jichuan Trading Co., Ltd.

Add: No 1201, Yinhai Building, Caoxi Road,
Xuhui District, Shanghai

24h Hotline: 15900706965

Website: www.pingyiao.com

Tel: (86) 021-64820099

Fax: (86) 021-64513829

E-mail: info@jichuan.sh.cn