

## Shanghai Jichuan Trading

9.

## LIQUIprime 5404

DESCRIPTION	LIQUI <i>prime</i> 5404 is a toluene-free adhesion promoter with accelerated adhesion development for plastics and paints. Liqui <i>prime</i> 5404 is used in direct glazing on vehicles with plastic bodywork and is used in conjunction with Liqui <i>mate</i> 8000			
	super adhesive.		$c O^{\circ}$	
PROPERTIES	<ul> <li>used for pretreating various r</li> <li>adhesion promoter for LIQUI</li> </ul>		•	
TECHNICAL			. 0.0	
DATA	Base	:	polyisocyanates	
	Color	:	black	
	Odor	:	characteristic	
	Pigments	¢:	lamp black	
	Density at 20 °C	:	0.9 g/cm³	
	Viscosity at 23 °C	:	< 16 seconds	
	Flash point	:	-8 °C	
	Boiling point	:	77 °C	
	Processing temperature	:	ideally 10 °C - 40 °C	
	Drying time	:	50 -150 seconds at 23 °C/50 % r.h.	
	Flash-off period	:	min. 10 minutes at 23 °C/50 % r.h. depending on the method of use; film must be dust dry max. 8 - 24 h depending on the type of LM	
used				
			Reactivation with LIQUI <i>prime</i> 5404 or LIQUI <i>wipe</i> 4001 possible	
N	Storage life	:	12 months in unopened containers	
Q,Y	Stability in containers which			
00	have been opened	:	100 ml: 5 days	
100,	Storage	:	Temperature: +5 °C - +25 °C short periods up to 40 °C	

APPLICATIONS

For treating different metal surfaces for bonding, especially for LIQUI*mate* 8000 super adhesive as well as direct glazing of vehicles with plastic bodywork.

Shanghai Jichuan Trading Co.,Ltd.				
Add: No 1201, Yinhai Building, Caoxi Road,	Tel: (86) 021-64820099			
Xuhui District, Shanghai				
24h Hotline: 15900706965	Fax: (86) 021-64513829			
Website: www.pingyiao.com	E-mail: info@jichuan.sh.cn			



## Shanghai Jichuan Trading

APPLICATION	Shake container well until t about another minute.	ne steel balls have worked free and then shake for	A		
	<u>Note</u> This product is very moistu	<u>Note</u> This product is very moisture sensitive. Containers which have been opened must be closed again immediately after			
	Preparing the bonding surf	ace es with Cleaner and Thinner.			
AVAILABLE PACK SIZE	LIQUI <i>prime</i> 5404	100 ml Aluminum bottle: Part. no. 6131			
	Processing equipment Applicators/woolen wiping	sloth, Part no. 6203			
		42001			
	HUNDS	▶			
25					
Shangh					

Shanghai Jichuan Trading Co.,Ltd.Add: No 1201, Yinhai Building, Caoxi Road,Xuhui District, Shanghai24h Hotline: 15900706965Website: www.pingyiao.com

Tel: (86) 021-64820099

Fax: (86) 021-64513829 E-mail: info@jichuan.sh.cn