



Shanghai Jichuan Trading

Hohlraumversiegelung braun (Aerosol) (Cavity Protection, brown (aerosol))

DESCRIPTION

Cavity Protection brown is a solvent-based corrosion inhibitor for cavity protection. It is available as a thin, light thixotropic spray with good atomizing properties which, by using the fine spray tube suspended in the lid, can also reach narrow gaps between metal panels. Cavity Protection brown infiltrates and displaces moisture. The product contains a high proportion of rust inhibitors. Cavity Protection brown is very finely atomized during spraying, has outstanding creep properties, penetrates well into narrow gaps which need protection (such as welded seams) but does not run significantly out of seams. On drying completely, the product forms a very tough, permanently soft, water-repellent pale brown film which is almost transparent.

PROPERTIES

- high creep
- short follow-up time
- ideal for rust protection on welded body components
- outstanding corrosion protection
- infiltrates and displaces moisture
- good heat resistance

TECHNICAL DATA

Base	:	Wax	
Color	:	pale brown	
Odor	:	characteristic	
Consumption	:	20	m ² /l
Drying time	:	approx. 2 - 3	hours
Corrosion resistance			
Salt-spray test ASTM B 117	:	above 500	hours
Solids content	:	35	%
Dropping point for the solid	:	90	°C
Rigidity	:	200 - 300	µm
Processing temperature	:	15 °C - 25 °C	
Heat resistance	:	-40 °C to +90 °C	
Risk of frost damage	:	no	
Recommended storage temperature	:	5 °C - 25 °C	
Storage time	:	24 months	

Shanghai Jichuan Trading Co.,Ltd.

Add: No 1201, Yin Hai Building, Caoxi Road, Xuhui District, Shanghai

24h Hotline: 15900706965

Website: www.pingyiao.com

Tel: (86) 021-64820099

Fax: (86) 021-64513829

E-mail: info@jichuan.sh.cn



Shanghai Jichuan Trading

APPLICATIONS

In the workshop, the product is mainly used for spraying the inner surfaces of cavities, such as frame side members and doors, for supplementing existing cavity protection in new vehicles and for the aftertreatment of cavity protection after accident repairs. By using the available spray head, the corrosion inhibitor can also be sprayed onto surfaces such as the underbody giving them a high level of rust protection and a fresh "as new" appearance.

APPLICATION

Any rust which may be present on the surfaces to be treated must be thoroughly removed before treatment. The spray head with the spray extension may be used to reach relatively inaccessible surfaces. The material must be at room temperature when used.

Shake the can vigorously before use.

When the ball has worked loose, continue to shake the can for a further minute.

Hold the can vertically when spraying and spray thinly at a distance of about 20-30 cm from the surface. After use, the can must be inverted and sprayed until the valve is clear, with only propellant escaping.

AVAILABLE PACK SIZE

Cavity Protection
brown

500 ml aerosol

Part. no. 6107

Shanghai Jichuan Trading Co.,Ltd.

Add: No 1201, Yinhai Building, Caoxi Road, Xuhui District, Shanghai

24h Hotline: 15900706965

Website: www.pingyiao.com

Fax: (86) 021-64513829

E-mail: info@jichuan.sh.cn



Shanghai Jichuan Trading

Shanghai Jichuan Trading Co., Ltd.

Shanghai Jichuan Trading Co.,Ltd.

Add: No 1201, Yinhai Building, Caoxi Road, Xuhui District, Shanghai

24h Hotline: 15900706965

Website: www.pingyiao.com

Fax: (86) 021-64513829

E-mail: info@jichuan.sh.cn