

Shanghai Jichuan Trading

Hydraulic tappet additive (Hydro-Stößel-Additiv)

DESCRIPTION High performance additive that damps down noise generation of contaminated and

sticky hydraulic tappets. Cleans valve bores and thus ensures optimal functioning

again.

PROPERTIES - improves the lubrication properties of the oil

- cleans valve bores

- suitable for use in vehicles with turbochargers and vehicles with catalytic

converters

- prevents engine noises caused by hydraulic tappets

TECHNICAL Color : yellowish DATA Appearance : viscous liqu

Appearance : viscous liquid
Density at +20 °C : 0.895 g/cm³

Density at +20 °C : 0.895 g/cm³ DIN 51757 Viscosity at +40 °C : 510 mm²/s DIN 51562

AREAS OF For all gasoline and diesel engines. Can be mixed with all commercially available

APPLICATION motor oils

APPLICATION One 300 ml can of Liqui Moly hydraulic tappet additive is sufficient for up to 6 liters

motor oil. The product can be added at any time. After adding, run the engine until warm. For a lasting effect, Liqui Moly Hydraulic tappet additive must be added after

each oil change.

Note:

Not suitable for use on motorbikes with wet clutches.

AVAILABLE

PACK SIZES Hydraulic tappet additive 300 ml Part no. 1009

Shanghai Jichuan Trading Co.,Ltd.

Add: No 1201, Yinhai Building, Caoxi Road, Tel: (86) 021-64820099

Xuhui District, Shanghai

24h Hotline: 15900706965 Fax: (86) 021-64513829 Website: www.pingyiao.com E-mail: info@jichuan.sh.cn



Shanghai Jichuan Trading

Shandhai Jichilan Tradinis

Shanghai Jichuan Trading Co.,Ltd.

Add: No 1201, Yinhai Building, Caoxi Road, Tel: (86) 021-64820099

Xuhui District, Shanghai

24h Hotline: 15900706965 Fax: (86) 021-64513829 Website: www.pingyiao.com E-mail: info@jichuan.sh.cn