



Shanghai Jichuan Trading

Oil Additive

DESCRIPTION

Colloidal solid lubricant suspension based on molybdenum sulfide (MoS₂) in mineral oil. The product forms a high-load lubricating film on all rubbing and sliding surfaces. This in turn reduces friction, providing for smoother operation of assemblies and greater engine economy. Tested for turbochargers and catalytic converters.

PROPERTIES

- Mixable with all commercially available motor oils
- Stable even under high thermal and dynamic permanent loads
- No deposits and absolutely compatible with all commonly used filter systems
- Reduces running-in and running wear
- Guarantees limp-home properties
- Reduces oil and fuel consumption
- Increases smooth operation

TECHNICAL DATA

Base (LM 41 MoS ₂ suspension)	:	MoS ₂ suspension	
Color	:	gray-black	
MoS ₂ specifications	:	complies with MIL-M-7866 B, DEF 2304, CS 2819	
MoS ₂ particle size	:	Majority < 0.3 μm	
Solids content	:	approx. 3	%
Density at +20 °C	:	0.89 - 0.90	g/cm ³ DIN 51757
Viscosity at +20 °C	:	~300	mPa*s DIN 51398
Flash point	:	200	°C DIN ISO 2592
Pour point	:	-20	°C DIN ISO 3016

AREAS OF APPLICATION

Added to the lubricating oils of engines, compressors, pumps and especially motor vehicle engines (gasoline and diesel). Mixable with all commercially available motor oils.

APPLICATION

Add 5 % (50 ml per liter of oil) of Oil Additive to motor oil; in motorcycles with wet clutch, add 2 % (20 ml per liter of oil). Can be added to motor oil at any time. **The maximum dosage for motorcycles with a wet clutch is 2 %!**

AVAILABLE PACK SIZES

Oil Additive	125 ml	Part no. 1011
	200 ml	Part no. 1012
	500 ml	Part no. 1013
	5 ltrs.	Part no. 3710
	205 ltrs.	Part no. 3749

Shanghai Jichuan Trading Co.,Ltd.

Add: No 1201, Yin Hai Building, Caoxi Road,
Xuhui District, Shanghai

24h Hotline: 15900706965

Website: www.pingyiao.com

Tel: (86) 021-64820099

Fax: (86) 021-64513829

E-mail: info@jichuan.sh.cn



Shanghai Jichuan Trading

Shanghai Jichuan Trading Co., Ltd.

Shanghai Jichuan Trading Co., Ltd.

Add: No 1201, Yin Hai Building, Caoxi Road,
Xuhui District, Shanghai

24h Hotline: 15900706965

Website: www.pingyiao.com

Tel: (86) 021-64820099

Fax: (86) 021-64513829

E-mail: info@jichuan.sh.cn