

## Shanghai Jichuan Trading

## Getriebeöl-Additiv (Gear Oil Additive)

**DESCRIPTION** Gear Oil Additive is a

Gear Oil Additive is a stabilised solid lubricant concentrate in mineral oil. Due to its high MoS<sub>2</sub> content and special additives, it is suitable for all manual motor vehicle transmissions and for axle drives without self-locking differential.

**PROPERTIES** 

- reduces friction and wear

improves gear change performancestable under continuous high loads

boosts operating reliabilityreduces transmission noise

- increases smoothness and limp-home properties

- secures optimum transmission operation

TECHNICAL DATA

Colour : grey-black

content Solidsapprox. 10 %

Viscosity at 20 °C 380 mPa\*s

Operating temperature

range depends on the oil used

MoS<sub>2</sub> : above 400 °C

Flash point: > 200°C

Pour point : -15 °C

**APPLICATION** 

Added to motor vehicle manual transmissions, axle drives, differential transmissions and mechanical steering systems. Not suitable for fully automatic transmissions and

self-locking differential transmissions.

**INSTRUCTIONS** 

Add Gear Oil Additive to the gear oil — mixing takes place automatically during operation. The product is suitable for both mineral- and synthetic-based gear oils. One tube is sufficient for up to 2 litres of gear oil (corresponds to a concentration of

1 wt %). In extreme cases, add at a rate of 2 %.

AVAILABLE

PACK SIZE Gear Oil Additive 20 g tube Part no. 1040

Shanghai Jichuan Trading Co., Ltd.

Add: No 1201, Yinhai Building, Caoxi Road, Tel: (86) 021-64820099

Xuhui District, Shanghai

24h Hotline: 15900706965 Fax: (86) 021-64513829

Website: www.pingyiao.com E-mail: info@jichuan.sh.cn



## Shanghai Jichuan Trading

Shangt 18

Shanghai Jichuan Trading Co.,Ltd.

Add: No 1201, Yinhai Building, Caoxi Road,

Xuhui District, Shanghai

24h Hotline: 15900706965 Fax: (86) 021-64513829

Website: www.pingyiao.com E-mail: info@jichuan.sh.cn

Tel: (86) 021-64820099