



Shanghai Jichuan Trading

Diesel Anti-Knock

DESCRIPTION

Diesel Anti-Knock is a combination of additives with cleaning, dispersing, and material-protecting characteristics and cetan-number increasing properties, matched to present-day engines, automotive fluids and operating conditions. Due to the increased ignition performance, the fuel shows better combustion behavior when the engine is cold and the pollution from odors in the exhaust gases is reduced.

PROPERTIES

- Cleans thoroughly and prevents deposits from forming in fuel systems and combustion chambers
- Keeps the injectors clean and guarantees improved engine combustion leading to a lower specific fuel consumption and the maximum engine performance
- Prevents seizing and the injector needles from gumming up
- Increases the lubrication action of diesel fuels low in sulphur (low sulphur diesel in accordance with DIN EN 590) and protects distributor injector pumps from wear
- Increases the cetane number of diesel fuel, leading to a smooth and gentle combustion process
- Contains antioxidant and prevents corrosion
- Compatible with all modern diesel oxidation catalytic converters

TECHNICAL DATA

Base	: additive mixture in carrier fluid
Color	: yellowish brown
Density at 15 °C	: 0.84 g/cm ³
Regulation on flammable liquids (German)	: A III
Flash point	: 63 °C
Pour point	: -36 °C

APPLICATIONS

Added to diesel fuel for all diesel engines, particularly in modern high pressure injection engines such as common-rail and pumped-jet fuel injection engines in passenger and commercial motor vehicles, tractors, construction machinery and stationary engines. Ideally suitable for preserving engines when decommissioned for long periods under extreme conditions.

Shanghai Jichuan Trading Co.,Ltd.

Add: No 1201, Yin Hai Building, Caoxi Road, Tel: (86) 021-64820099
Xuhui District, Shanghai

24h Hotline: 15900706965

Fax: (86) 021-64513829

Website: www.pingyiao.com

E-mail: info@jichuan.sh.cn



Shanghai Jichuan Trading

APPLICATION

- One 250 ml can of the product is sufficient to treat 75 liters of diesel fuel. Dosage: 1:300.
- To keep the injectors clean and for corrosion protection, add Diesel Anti-Knock to the passenger vehicle diesel fuel tank every 2,000 km.
- The 205 liter drums are for trucks, transport companies, bus companies and industry. The dosage rate is in the proportion 1:300 additive to diesel fuel.
- When decommissioning and preserving engines, add Diesel Anti-Knock to the diesel fuel at the rate of 1 %. Follow the instructions on preservation.
- Diesel Anti-Knock can be mixed with the fuel at any time since mixing takes place automatically.

AVAILABLE PACK SIZES

Diesel Anti-Knock

250 ml	Part no.	2504
205 ltrs.	Part no.	2814
205 ltrs.	Part no.	5146

Shanghai Jichuan Trading Co.,Ltd.

Add: No 1201, Yin Hai Building, Caoxi Road, Tel: (86) 021-64820099
Xuhui District, Shanghai

24h Hotline: 15900706965

Fax: (86) 021-64513829

Website: www.pingyiao.com

E-mail: info@jichuan.sh.cn