

Shanghai Jichuan Trading

Cera Tec

DESCRIPTION

Micro ceramic solid lubricant suspension based on hexagonal boron nitride (BN) in mineral oil. The laminar graphite-similar structure reduces friction and wear and prevents direct metal-to-metal contact. The < 0.5 μ m particle size guarantees optimal filter flow properties and protects against depositing of solid lubricant particles.

PROPERTIES

- Mixable with all commercially available motor oils
- Stable even under high thermal and dynamic permanent loads
- No deposits and absolutely compatible with all commonly used filter systems
- Resists extremely high and low temperatures
- Reduces fuel consumption
- Increases engine service life
- Increases smooth operation
- Stable under extreme pressures
- Chemically inert
- Higher performance gain due to reduced friction
- Does not increase the phosphorous and sulfur content of the motor oil

TECHNICAL DATA

Base

: BN micro ceramic Color:: Yellowish white

Ceramic particle size

: Majority < 0.5 µm

Temperature stability of the

ceramic particles : To +1,200 °C

Density at +20 °C : 0-89 - 0.90 DIN 51757 g/cm³ Viscosity at +20 °C : ~300 mPa*s DIN 51398 Flash point : 200 °C **DIN ISO 2592** Pour point : -20 °C **DIN ISO 3016**

APPLICATIONS

Added to the lubricating oil of engines, compressors, pumps and transmissions. Excellent for use in passenger car and commercial vehicle engines (gasoline and diesel). Mixable with all commercially available motor oils.

Tel: (86) 021-64820099

APPLICATION

300 ml will treat up to 5 liters of motor oil. Long-term effect up to 50,000 km.

Note:

Not suitable for use with wet clutches!

AVAILABLE

PACK SIZES Cera Tec 300 ml can Part no. 3721

Shanghai Jichuan Trading Co., Ltd.

Add: No 1201, Yinhai Building, Caoxi Road,

Xuhui District, Shanghai

24h Hotline: 15900706965 Fax: (86) 021-64513829

Website: www.pingyiao.com E-mail: info@jichuan.sh.cn



Shanghai Jichuan Trading

Shara A

Shanghai Jichuan Trading Co.,Ltd.

Add: No 1201, Yinhai Building, Caoxi Road,

Xuhui District, Shanghai

24h Hotline: 15900706965 Fax: (86) 021-64513829

Website: www.pingyiao.com E-mail: info@jichuan.sh.cn

Tel: (86) 021-64820099