



Shanghai Jichuan Trading

Diesel Lubrication Additive

DESCRIPTION

With the majority of low-sulphur diesel fuels, wear in the fuel-lubricated distributor injection pumps which are installed in passenger vehicles and small heavy goods vehicles is increased if lubricant additives are not added to the diesel fuel. Diesel Lubrication Additive is a combination of agents which has been especially developed for low-sulphur diesel fuels to help reduce wear in the fuel-lubricated distributor injection pumps.

PROPERTIES

- reduces sliding and vibration wear
- increases the service life and operation time of distributor pumps
- prevents injection pressure loss
- compatible with diesel-oxidation catalytic converters
- simple to use
- cost effective and does not pollute the environment

TECHNICAL DATA

Base	: Special additive formulation
Color	: Pale/yellow
Density at 15 °C	: 0.81 g/cm ³
Viscosity at 40 °C	: 1.8 mm ² /s
Flash point	: 63 °C

AREAS OF APPLICATION

Can be used with all low-sulphur diesel fuels and diesel fuels with normal sulphur content.

APPLICATION

Added before or after filling up with fuel. 150 ml pack sufficient for 80 l of diesel fuel. Dosage 1:533

AVAILABLE PACK SIZES

Diesel Lubrication Additive	150 ml	Part no. 5122
-----------------------------	--------	---------------

Shanghai Jichuan Trading Co.,Ltd.

Add: No 1201, Yin Hai Building, Caoxi Road, Xuhui District, Shanghai

24h Hotline: 15900706965

Fax: (86) 021-64513829

Website: www.pingyiao.com

E-mail: info@jichuan.sh.cn