



Shanghai Jichuan Trading

Diesel fließ-fit (Diesel Flow Fit)

DESCRIPTION

Diesel Flow Fit is a combination of different high-molecular, ash-free additives in a carrier fluid. This product controls the growth of paraffin crystals caused by the cold significantly improving the filtration properties and pour point of diesel fuel in cold weather. The effectiveness of the flow improver is dependent on the type of paraffin and the paraffin content of the medium distillates.

PROPERTIES

- secures winter operation which would otherwise be affected by the cold
- improves the filtration properties of diesel fuel
- suitable for all diesel fuels (summer and winter diesel grades according to DIN EN 590)
- simple to use and economical
- high response with diesel fuels

TECHNICAL DATA

Colour	: pale/clear	
Density at 20 °C	: 0.90	g/cm ³
Viscosity at 20 °C	: 3.6	mm ² /s
Ash content	: 0.01	(wt %)
Flash point	: 64	°C
Pour point	: - 21	°C
Improvement in filtration EN 116	: up to 10 °C, depending on diesel quality	
Dosage	: 150 ml portion pack sufficient for 50 litres diesel fuel, corresponds to 1:330	

APPLICATION

Used for all grades of diesel fuel to secure winter operation which would otherwise be affected by the cold in passenger and commercial motor vehicle diesel engines as well as buses, construction machinery and stationary diesel engines.

INSTRUCTIONS

For optimum effect in preventing paraffin separation, it is necessary to add the flow improver approx. 5 °C before the cloud point (turbidity point) is reached.

To improve mixing, add Diesel Flow Fit before filling up with fuel.

Clusters of paraffin crystals which have already formed in the tank cannot be broken up by adding Diesel Flow Fit.

AVAILABLE PACK SIZE

Diesel Flow Fit	150 ml	Part no. 5130
	150 ml	Part no. 1877

Shanghai Jichuan Trading Co.,Ltd.

Add: No 1201, Yin Hai Building, Caoxi Road, Xuhui District, Shanghai

24h Hotline: 15900706965

Website: www.pingyiao.com

Tel: (86) 021-64820099

Fax: (86) 021-64513829

E-mail: info@jichuan.sh.cn



Shanghai Jichuan Trading

Shanghai Jichuan Trading Co., Ltd.

Shanghai Jichuan Trading Co., Ltd.

Add: No 1201, Yin Hai Building, Caoxi Road, Xuhui District, Shanghai

24h Hotline: 15900706965

Website: www.pingyiao.com

Tel: (86) 021-64820099

Fax: (86) 021-64513829

E-mail: info@jichuan.sh.cn