



Systempflege Diesel (Diesel System Treatment)

DESCRIPTION

Diesel System Treatment is a combination of agents with a high proportion of lubrication improvers and cleaners. This product is therefore specially formulated to meet the demands of diesel engines with Common Rail high pressure injection using low sulphur diesel fuels and to give protection against wear. Other agents which have cleaning, dispersion and material protection properties maintain the operation of high-precision injectors. Due to the increased ignition performance, the fuel shows better combustion behaviour when the engine is cold and the pollution from odours in the exhaust is reduced.

PROPERTIES

- keeps fuel system and combustion chambers clean and prevents deposits from forming
- keeps the injectors clean and guarantees improved engine combustion leading to a lower specific fuel consumption and the maximum engine performance.
- prevents seizing and resinifying of the injector needles.
- increases the lubrication action of diesel fuels low in sulphur (low sulphur diesel according to DIN EN 590) and protects high-pressure pumps from wear
- increases the cetan number of diesel fuel leading to a smooth and gentle combustion process
- contains antioxidant and prevents corrosion
- compatible with all modern diesel oxidation catalytic converters

TECHNICAL DATA

Basis	: additive mixture in carrier fluid
Density at 15 °C	: 0.846 g/cm ³
Colour	: brown
Regulation on flammable liquids (Germany)	: A III
Flash point	: 62 °C
Pour point	: -36 °C

APPLICATION

Added to diesel fuel for all diesel engines with Common Rail injection. Ideally suitable for preserving engines when decommissioned for long periods under extreme conditions.

Shanghai Jichuan Trading Co.,Ltd.

Add: No 1201, Yin Hai Building, Caoxi Road,
Xuhui District, Shanghai

24h Hotline: 15900706965

Website: www.pingyiao.com

Tel: (86) 021-64820099

Fax: (86) 021-64513829

E-mail: info@jichuan.sh.cn



Shanghai Jichuan Trading

INSTRUCTIONS

- The ignition performance is increased and the lubrication action and lubricity performance are improved only by adding the product to low-sulphur diesel fuels on a continual basis. One 250 ml can of the product is sufficient for 75 litres of fuel. Dosage 1:300
- To keep the injectors clean and for corrosion protection, add Diesel System Treatment to the passenger vehicle diesel fuel tank every 2,000 km.
- When decommissioning and preserving engines, add Diesel System Treatment to diesel fuel at the rate of 1 %. Follow the instructions on preservation.
- Diesel System Treatment can be mixed with the fuel at any time since mixing takes place automatically.

AVAILABLE PACK SIZE

Diesel System Treatment 250 ml Part no. 5139

Shanghai Jichuan Trading Co.,Ltd.

Add: No 1201, Yin Hai Building, Caoxi Road,
Xuhui District, Shanghai

24h Hotline: 15900706965

Website: www.pingyiao.com

Tel: (86) 021-64820099

Fax: (86) 021-64513829

E-mail: info@jichuan.sh.cn