



Shanghai Jichuan Trading

7ySuper Diesel Additiv mit Lubricity Improver (Super Diesel Additive with Lubricity Improver)

DESCRIPTION

Super Diesel Additive with Lubricity Improver contains a mixture of agents with cleaning, dispersing, material-protection and cetan-number increasing properties which has been formulated for today's engines, fuels and running conditions. The resulting Lubricity Improver provides better lubricity for diesel fuels low in sulphur. Due to the increased ignition performance, the fuel shows better combustion behaviour when the engine is cold and the pollution from odours in the exhaust is reduced.

PROPERTIES

- keeps fuel system and combustion chambers clean and prevents deposits from forming
- keeps the injectors clean and guarantees improved engine combustion leading to a lower specific fuel consumption and the maximum engine performance
- prevents seizing and the injector needles from resinifying
- increases the lubrication action of diesel fuels low in sulphur (low sulphur diesel in accordance with DIN EN 590) and protects distributor injector pumps from wear
- increases the cetan number of diesel fuel, leading to a smooth and gentle combustion process
- contains antioxidant and prevents corrosion
- compatible with all modern diesel oxidation catalytic converters

TECHNICAL DATA

Basis	: additive mixture in liquid carrier
Colour	: yellowish brown
Density at 15 °C	: 0.84 g/cm ³
German VbF hazard class	: A III
Flash point	: 63 °C
Pour point	: -36 °C

APPLICATION

Added to diesel fuel for all diesel engines, particularly in modern high pressure engines in passenger and commercial motor vehicles, tractors, construction machinery and stationary engines. Ideally suitable for preserving engines when decommissioned for long periods under extreme conditions.

Shanghai Jichuan Trading Co.,Ltd.

Add: No 1201, Yin Hai Building, Caoxi Road, Xuhui District, Shanghai

24h Hotline: 15900706965

Website: www.pingyiao.com

Fax: (86) 021-64513829

E-mail: info@jichuan.sh.cn



Shanghai Jichuan Trading

INSTRUCTIONS

- The ignition performance is increased and the lubrication action and Lubricity Performance improved by adding the product to low-sulphur diesel fuels on a continual basis. One 250 ml can of the product is sufficient for 75 litres of fuel. Dosage rate: 1:300.
- To keep the injectors clean and for corrosion protection, Super Diesel Additive with Lubricity Improver is added to the passenger vehicle diesel tank every 2,000 km.
- The 5 litre canisters and 50 litre drums are for HGVs, transport companies, bus companies and industry. The dosage rate is in the proportion 1:300 additive to diesel fuel
- When decommissioning and preserving engines, add Super Diesel Additive with Lubricity Improver to diesel fuel at the rate of 1 %. Follow the instructions on preservation.
- Super Diesel Additive can be mixed with the fuel at any time since mixing takes place automatically.

AVAILABLE PACK SIZE

Super Diesel Additive
with Lubricity Improver

250 ml

5 l

canister

50 l

drum

Part no. 5120

Part no. 5140

Part no. 5145

Shanghai Jichuan Trading Co.,Ltd.

Add: No 1201, Yin Hai Building, Caoxi Road, Xuhui District, Shanghai

24h Hotline: 15900706965

Website: www.pingyiao.com

Tel: (86) 021-64820099

Fax: (86) 021-64513829

E-mail: info@jichuan.sh.cn