



meguinfo

Art.-Nr. 2202.000

Stand: 00.04

megol Hydraulikoel HLP 22

HLP hydraulic oils are mineral oils that are used as pressure fluids in hydraulic systems. They contain active ingredients to increase ageing resistance, anti-corrosive properties and EP properties. As a result of these additives they satisfy all requirements and are primarily used in hydraulic systems in which high thermal stresses occur, corrosion can form due to water and whose pumps or hydraulic motors require oil types with wear protection agents for mixed friction as a result of the operating conditions.

Approvals / Specifications: Hydraulic Oil DIN 51524 – HLP 22
Hydraulic Oil SEB 181 222 – HLP 22

Characteristic data

Approx. values

ISO viscosity class	DIN 51519		VG 22
Viscosity at 0°C	DIN 51562	mm ² /s	220
Viscosity at 40°C	DIN 51562	mm ² /s	22
Viscosity at 100°C	DIN 51562	mm ² /s	4,3
Viscosity index	DIN ISO 2909		100
Colour pursuant to ASTM	DIN 51578		1,5
Density at 15°C	DIN 51757	kg/m ³	880
Flash point	DIN ISO 2592	°C	206
Pour point	DIN ISO 3016	°C	-26
Ash, oxide	DIN EN 7	g/100 g	0.16
Ash, sulphate	DIN 51575	g/100 g	0.17
Coke residue using the Conradson method with ash	DIN 51551	g/100 g	0.18
Content of asphaltenes	DIN 51595	g/100 g	m.n.n. *)
Content of undissolved substances	DIN 51592	g/100 g	m.n.n. *)
Water content	DIN ISO 3733	g/100 g	m.n.n. *)
Neutralisation index, acid	DIN 51558 Part 1	mg KOH/g	0.5
Corrosive effect on steel	DIN 51585	degree of corrosion	0-B
Corrosive effect on copper	DIN 53538 Part 1	Vickers pump test	
Ageing properties	after	Wear after 250 h	
Neutralisation index after 1000 h	7 days at 100°C		
Foaming properties	Motor vehicle brief		
	gear test		
	Standard test		
Properties against sealing material SRE-NBR 1 pursuant to	A/8.3/90		*) m.n.n. = Quantity not detectable

Shanghai Jichuan Trading Co.,Ltd.

Add: No 1201, Yin Hai Building, Caoxi Road,
Xuhui District, Shanghai

24h Hotline: 15900706965

Website: www.pingyiao.com

Tel: (86) 021-64820099

Fax: (86) 021-64513829

E-mail: info@jichuan.sh.cn



Shanghai Jichuan Trading

DIN 51759	degree of corrosion 125 A3	1-
DIN 51587	mg KOH/g	<
DIN 51566	2	
	S1B-30/0	
Change in volume	S2B-50/0	
Change in hardness	S3B-30/0	
DIN 51354		
Failure load level		
Unit weight change		
V 105 C	%-by-vol.	+
Ring	4	
	Shore	-
	3	
		1
		0
	mg/kWh	<
	0.27	
	mg	
		5
	0 mg	
	Blade	
	12	

Shanghai Jichuan Trading Co.,Ltd.

Add: No 1201, Yin Hai Building, Caoxi Road,
Xuhui District, Shanghai

24h Hotline: 15900706965

Website: www.pingyiao.com

Tel: (86) 021-64820099

Fax: (86) 021-64513829

E-mail: info@jichuan.sh.cn