



meguinfo

Art.-Nr. 2246.000

Stand: 95.08

megol Hydraulikoel HVLP 68

megol hydraulic oil HVLP 68 with ageing, rust, foam and wear preventing additives and particularly good viscosity-temperature ratio. Particularly recommended for use in hydraulic systems which are exposed to large temperature fluctuations.

This is especially applicable to all types of building machinery such as for Poclain, Jumbo and Atlas excavators.

Approvals / Specifications: Hydraulic Oil DIN 51524 – HVLP 68

Characteristic data

Approx. values

ISO viscosity class	DIN 51519		68
Viscosity at 40°C	DIN 51562	mm ² /s	68
Viscosity at 100°C	DIN 51562	mm ² /s	11.1
Viscosity index	DIN ISO 2909		155
Colour pursuant to ASTM	DIN 51578		0.5
Density at 15°C	DIN 51757	kg/m ³	880
Flash point	DIN ISO 2592	°C	218
Pour point	DIN ISO 3016	°C	-32
Air separation capacity / 50°C	DIN 51381	min.	5
De-emulsifying capacity / 54°C	DIN 51599	min.	30
Ash, oxide	DIN EN 7	g/100 g	0.19
Ash, sulphate	DIN 51575	g/100 g	0.21
Coke residue using the Conradson method with ash	DIN 51551	g/100 g	0.25
Content of asphaltenes	DIN 51595	g/100 g	m.n.n. *)
Content of undissolved substances	DIN 51592	g/100 g	m.n.n. *)
Water content	DIN ISO 3733	g/100 g	m.n.n. *)
Neutralisation index, acid	DIN 51558 Part 1	mg KOH/g	1.0
Saponification index	DIN 51559	mg KOH/g	1.5
Corrosive effect on steel	DIN 51585	degree of corrosion	0-A
Corrosive effect on copper	Neutralisation index after 1000 h	Foaming properties	
Ageing properties			

Shanghai Jichuan Trading Co.,Ltd.

Add: No 1201, Yin Hai Building, Caoyi Road,
Xuhui District, Shanghai

24h Hotline: 15900706965

Website: www.pingyiao.com

Tel: (86) 021-64820099

Fax: (86) 021-64513829

E-mail: info@jichuan.sh.cn



Shanghai Jichuan Trading

Motor vehicle brief gear test Standard test A/8.3/90	DIN 51759	degree of corrosion	1-100 A3
Vickers pump test	DIN 51587	mg KOH/g	< 2.0
Wear after 250 h	DIN 51566		S1B-60/0 S2B-20/0 S3B-60/0
Shear stability, viscosity loss at 40°C after 250 cycles	DIN 51354 Part 2		11
*) m.n.n. = Quantity not detectable	Failure load level		< 0.27
	Unit weight change	mg/kWh	20
	V 105 C	mg	8.0
	Ring/Blade	%	
	DIN 51382		

Shanghai Jichuan Trading Co.,Ltd.

Add: No 1201, Yinhai Building, Caoxi Road,
Xuhui District, Shanghai

24h Hotline: 15900706965

Website: www.pingyiao.com

Tel: (86) 021-64820099

Fax: (86) 021-64513829

E-mail: info@jichuan.sh.cn



Shanghai Jichuan Trading

Shanghai Jichuan Trading Co., Ltd.

Shanghai Jichuan Trading Co., Ltd.

Add: No 1201, Yinhai Building, Caoxi Road,
Xuhui District, Shanghai

24h Hotline: 15900706965

Website: www.pingyiao.com

Tel: (86) 021-64820099

Fax: (86) 021-64513829

E-mail: info@jichuan.sh.cn
