



meguinfo

Art.-Nr. 2266.000

Stand:2004/12

megol Hydraulikoel ATF Dexron II D

Hydraulic fluid for automatic transmissions and hydraulic clutches which require a Dexron D type automatic transmission fluid. Guarantees perfect functioning of the fluid transmissions even under the most strenuous operating conditions and large temperature fluctuations. Also suitable for systems functioning under strenuous operating conditions.

Approvals / Specifications:

ZF TE-ML 03D, 04D, 11A, 14A, 17C
MAN 339-D
ZF TE-ML 09 (GM 6137M)
Allison C4
Caterpillar TO-2
Citroen
Denison
Dexron D
Ford M2C-166 H
Mercon

Characteristic data

Approx. values

Viscosity at 40°C	DIN 51562	mm ² /s	40
Viscosity at 100°C	DIN 51562	mm ² /s	8.0
Viscosity index	DIN ISO 2909		175
Colour			red
Density at 15°C	DIN 51757	kg/m ³	875
Flash point	DIN ISO 2592	°C	196
Pour point	DIN ISO 3016	°C	-42
Ash, oxide	DIN EN 7	g/100 g	0.22
Ash, sulphate	DIN 51575	g/100 g	0.30
Coke residue using the Conradson method with ash	DIN 51551	g/100 g	0.4
Shear stability, viscosity at 100°C after 20 h Vehicle A/16.6/90/5 h	CEC-TLPG7	mm ² /s	6.1
Base count	DIN ISO 3771	mg KOH/g	3.0

Shanghai Jichuan Trading Co.,Ltd.

Add: No 1201, Yin Hai Building, Caoxi Road,
Xuhui District, Shanghai

24h Hotline: 15900706965

Website: www.pingyiao.com

Tel: (86) 021-64820099

Fax: (86) 021-64513829

E-mail: info@jichuan.sh.cn