



meguinfo

Art.-Nr.: 2268.000

Stand: 05/04

megol Transmission-Fluid ATF III

Hydraulic fluid for automatic transmissions and hydraulic clutches which require a Dexron II E or Dexron III type automatic transmission fluid. Guarantees perfect functioning of the transmissions even under the most strenuous operating conditions and large temperature fluctuations. Also suitable for systems functioning under strenuous operating conditions.

Approvals Specifications:
ZF TE-ML 04D, 17C
Voith G 607
Allison C4
Caterpillar TO-2
Ford Mercon
GM Dexron III G
MAN 339-C

Characteristic data			Approx. values
Viscosity at -40°C	DIN 51398	mPa.s	18000
Viscosity at 40°C	DIN 51562	mm ² /s	36
Viscosity at 100°C	DIN 51562	mm ² /s	7.9
Viscosity index	DIN ISO 2909		205
Colour according to ASTM	DIN 51578		2.5
Density at 15°C	DIN 51757	kg/m ³	865
Flash point	DIN ISO 2592	°C	185
Pour point	DIN ISO 3016	°C	-46
Cinders, sulphate	DIN 51575	g/100 g	0.10
Shear resistance, viscosity at 100°C after shearing	DIN 51350-06-KRL/C	mm ² /s	5.1
Base number	DIN ISO 3771	mg KOH/g	2.0

Shanghai Jichuan Trading Co.,Ltd.

Add: No 1201, Yin Hai Building, Caoxi Road,
Xuhui District, Shanghai

24h Hotline: 15900706965

Website: www.pingyiao.com

Tel: (86) 021-64820099

Fax: (86) 021-64513829

E-mail: info@jichuan.sh.cn