



meguinfo

Art.-Nr. 2163.000

Stand: 00.05

megol Umlaufschmieröl C 5

Ageing resistant mineral oil mainly used for lubrication places with circulation lubrication and total loss lubrication.

Approvals / Specifications: lube oil DIN 51517 - C 5

Characteristic data

			approx. values
ISO viscosity class	DIN 51519		VG 5
Viscosity at 0°C	DIN 51562	mm ² /s	18,0
Viscosity at 40°C	DIN 51562	mm ² /s	4,8
Viscosity at 100°C	DIN 51562	mm ² /s	1,7
Density at 15°C	DIN 51757	kg/m ³	855
Flash point	DIN ISO 2592	°C	120
Pour point	DIN ISO 3016	°C	-26
Air separation capacity / 50°C	DIN 51381	min.	2
De-emulsifying capacity / 54°C	DIN 51599	min.	10
Ash, oxide	DIN EN 7	g/100 g	<0,01
Content of asphaltenes	DIN 51595	g/100 g	m.n.n.*)
Content of undissolved substances	DIN 51592	g/100 g	
Water content	DIN ISO 3733	m.n.n.*)	
Neutralisation index, acid	DIN 51558 Part 1	g/100 g	0,15
Foaming properties	DIN 51566	m.n.n.*) mg KOH/g	
Properties against sealing material SRE-NBR 1 pursuant to		S1B-80/0 S2B-40/0 S3B-80/0	
DIN 53538 Part 3 after 7 days at 100°C	Change in volume Change in hardness	%-by-vol. Shore	+10 -4

*) m.n.n. = Quantity not detectable

Shanghai Jichuan Trading Co.,Ltd.

Add: No 1201, Yin Hai Building, Caoxi Road,
Xuhui District, Shanghai

24h Hotline: 15900706965

Website: www.pingyiao.com

Tel: (86) 021-64820099

Fax: (86) 021-64513829

E-mail: info@jichuan.sh.cn