



meguinfo

Art.-Nr. 2165.000

Stand: 94.03

megol Getriebeoel CL 10

Ageing resistant mineral oils with corrosion- and oxidation protection additives, mainly for use on lubrication points with total loss or circulation lubrication.

Approvals / Specifications: lube oil DIN 51517 - CL 10

Characteristic data

approx. values

ISO viscosity class	DIN 51519		VG 10	
Viscosity at 0°C	DIN 51562	mm ² /s	50	
Viscosity at 40°C	DIN 51562	mm ² /s	10	
Viscosity at 100°C	DIN 51562	mm ² /s		2,65
Viscosity index	DIN ISO 2909		100	
Density at 15°C	DIN 51757	kg/m ³	858	
Flash point	DIN ISO 2592	°C	140	
Pour point	DIN ISO 3016	°C	-26	
Air separation capacity / 50°C	DIN 51381	min.	2	
De-emulsifying capacity / 54°C	DIN 51599	min.	10	
Ash, oxide	DIN EN 7	g/100 g	<0,01	
Coke residue Conradson method				
With ash	DIN 51551	g/100g	0,05	
Content of asphaltenes	DIN 51595	g/100 g	m.n.n.*)	
Content of undissolved substances	DIN 51592	g/100 g		
Water content	DIN ISO 3733	m.n.n.*)		
Neutralisation index, acid	DIN 51558 Part 1	g/100 g	0,2	
Corrosive effect on steel	DIN 51585	m.n.n.*) mg KOH/g degree of corrosion 0-A		
Corrosive effect on copper	DIN 51759	degree of corrosion 1-100 A3		
Ageing properties				
Neutralisation index after 1000	DIN 51587	mg KOH/g	<2,0	
Foaming properties	Properties against sealing material	SRE-NBR 1 pursuant to DIN 53538 Part 3 after 7 days at 100°C		

Shanghai Jichuan Trading Co.,Ltd.

Add: No 1201, Yinhai Building, Caoxi Road,
Xuhui District, Shanghai

24h Hotline: 15900706965

Website: www.pingyiao.com

Tel: (86) 021-64820099

Fax: (86) 021-64513829

E-mail: info@jichuan.sh.cn



Shanghai Jichuan Trading

*) m.n.n. = Quantity not detectable

DIN 51566

S1B-80/0
S2B-40/0
S3B-80/0

Change in volume
Change in hardness

%-by-vol.
Shore

+8
-3

Shanghai Jichuan Trading Co.,Ltd.

Add: No 1201, Yinhai Building, Caoxi Road,
Xuhui District, Shanghai

24h Hotline: 15900706965

Website: www.pingyiao.com

Tel: (86) 021-64820099

Fax: (86) 021-64513829

E-mail: info@jichuan.sh.cn