



meguinfo

Art.-Nr. 3110.000

Stand: 95.09

megol Dicht- und Trennfett (rot)

A calcium soap grease, produced from carefully selected base oils and special additives. Use as sealing grease (hydrant grease), also in damp and dusty operating conditions. Also well suited for use as releasing grease.

Service range from -40 °C to +60 °C

Characteristical data

approx. values

Appearance and properties

Soft, red,
transparent
supple

Saponification type			Ca
Drip point	DIN ISO 2176	°C	100
Consistency class	DIN 51818		2
Fulling penetration	DIN ISO 2137	0.1 mm	265-295
Fulling stability	DIN ISO 2137		
Difference after 5,000 and 60 DH		0.1 mm	< 15
Difference after 100,000 and 60 DH		0.1 mm	< 40
Properties in water	DIN 51807 Part 1		1 – 50
Anti-corrosion properties			
Emcor method	DIN 51802	Corr. level	0
Copper strip test	DIN 51811	Corr. level	1 – 90
Solid foreign bodies			
Test screen mesh 140 µ	DIN 51813	mg / kg	< 4
Water content	DIN ISO 3733	g / 100 g	< 1,2
Oil separation after 7 days and +40°C	DIN 51817	g / 100 g	2,6

Shanghai Jichuan Trading Co.,Ltd.

Add: No 1201, Yinhai Building, Caoxi Road,
Xuhui District, Shanghai

24h Hotline: 15900706965

Website: www.pingyiao.com

Tel: (86) 021-64820099

Fax: (86) 021-64513829

E-mail: info@jichuan.sh.cn