



## *meguinfo*

Art.-Nr. 3111.000

Stand: 00.09

### **megol Dicht- und Trennfett (naturfarben)**

A calcium soap grease, produced from carefully selected base oils and special additives. Use as sealing grease (hydrant grease), also in damp and dusty operating conditions. Also well suited for use as releasing grease and corrosion protection grease.  
Service range from -40 °C to +60 °C

#### Characteristic data

approx. values

#### Appearance and properties

Soft, natural colour,  
transparent, supple

			Ca
Saponification type			
Base oil			
Viscosity at 40°C	DIN ISO 2592	°C	160
Drip point	DIN ISO 2176	°C	100
Consistency class	DIN 51818		2
Fulling penetration	DIN ISO 2137	0.1 mm	265-295
Fulling stability	DIN ISO 2137		
Difference after 5,000 and 60 DH		0.1 mm	< 15
Flashpoint	DIN ISO 2592	°C	210
Difference after 100,000 and 60 DH		0.1 mm	< 40
Properties in water	DIN 51807 Part 1		1 – 50
Anti-corrosion properties			
Emcor method	DIN 51802	Corr. level	0
Copper strip test	DIN 51811	Corr. level	0
Solid foreign bodies			
Test screen mesh 140 µ	DIN 51813	mg / kg	< 4
Water content	DIN ISO 3733	g / 100 g	< 1,2
Neutralisation index, alkaline	DIN 51809 Part 1	mg KOH/g	2,0
Oil separation after 7 days and +40°C	DIN 51817	g / 100 g	2,0
Pourpoint	DIN ISO 3016	°C	- 30
Ash, Oxide	DIN EN 7	g / 100 g	1,8
Ash, Sulphate	DIN 51803	g / 100 g	4,0

Shanghai Jichuan Trading Co.,Ltd.

Add: No 1201, Yinhai Building, Caoxi Road,  
Xuhui District, Shanghai

24h Hotline: 15900706965

Website: [www.pingyiao.com](http://www.pingyiao.com)

Tel: (86) 021-64820099

Fax: (86) 021-64513829

E-mail: [info@jichuan.sh.cn](mailto:info@jichuan.sh.cn)