



meguinfo

Art.-Nr. 3204.000

Stand: 04.01

megol Schmierfett BJ

megol grease BJ is used for life-long lubrication in fixed and moving joints.

The grease meets the Ford-Specification SMIC-9004A and the VW-Specification VW TL 738 for normal temperatures.

Service use from -35 °C to +130 °C

Characteristic data

Appearance and properties

Saponification type

base oil viscosity at 40 °C

Flash point

Pour point

Drip point

Consistency class

drafty

DIN 51562

DIN ISO 2592

DIN ISO 3016

DIN ISO 2176

DIN 51818

mm²150

°C

°C

°C

0,1 mm

DIN ISO 2137

DIN ISO 2137

Difference after 5.000 u. 60 DH

Difference after 100.000 u. 60 DH

0,1 mm

0,1 mm

Property against water

DIN 51807 part 1

Ant-corrosion properties

Emcor-method

Copper strip test

DIN 51802

DIN 51811

Corr.-degr.

Corr.-degr.

Water content

DIN ISO 3733

g / 100 g

Flowpressure at - 35 °C

DIN 51805

hPa

Oxidation resistance

Pressure fall after 100 h at + 99 °C

DIN 51808

bar

approx. values

grey-black, supple,

Li

224

- 22

180

2

290

< 10

< 20

1-90

0/1

< 0,1

< 1500

< 0,5

Shanghai Jichuan Trading Co.,Ltd.

Add: No 1201, Yin Hai Building, Caoxi Road,
Xuhui District, Shanghai

24h Hotline: 15900706965

Website: www.pingyiao.com

Tel: (86) 021-64820099

Fax: (86) 021-64513829

E-mail: info@jichuan.sh.cn