



meguinfo

Art.-Nr. 3213.000

Stand: 94.12

megol Getriebefließfett GP00H-25

A sodium soap liquid gear grease, produced from carefully selected base materials and special additives. It contains wear-reducing additives and excels through good corrosion protection ability. For use in gears which require grease lubrication.

Service range from -25 °C to +100 °C.
Brief temperature-peaks up to +120 °C are permissible.

Identification acc.to DIN 51502: GP00H-25

Approval: lubrication grease DIN 51826 GP00H-25

Characteristic data

approx. values

Appearance and properties

natural colour, half-flowing, long-

Saponification type

base oil viscosity at 40 °C

drawing

Flash point

Pour point

Drip point

Consistency class

DIN 51562

DIN ISO 2592

DIN ISO 3016

DIN ISO 2176

DIN 51818

mm²220

°C

°C

°C

Na

240

- 20

150

00

Fulling penetration

DIN ISO 2137

0,1 mm

405-425

Fulling stability

DIN ISO 2137

Difference after 5.000 u. 60 DH

0,1 mm

< 30

Difference after 100.000 u. 60 DH

0,1 mm

< 40

Anti-corrosion properties

Emcor-method

DIN 51802

Corr.-degr.

0

Copper strip test

DIN 51811

Corr.-degr.

1-100

solid foreign bodies

Test screen mesh 140 µ

DIN 51813

< 4

Water content

DIN ISO 3733

mg / kg

< 0,1

Ashes, oxide

DIN EN 7

g / 100 g

1,0

g / 100 g

Special weight change

VKA welding power

DIN 51350 T4

FZG- gear test , short

DIN 51354

Normal test A/2,8/90

failure load level

Shanghai Jichuan Trading Co.,Ltd.

Add: No 1201, Yinhai Building, Caoxi Road,
Xuhui District, Shanghai

24h Hotline: 15900706965

Website: www.pingyiao.com

Tel: (86) 021-64820099

Fax: (86) 021-64513829

E-mail: info@jichuan.sh.cn



Shanghai Jichuan Trading

N 3000/3200

mg/KWh 12
< 0,27

Shanghai Jichuan Trading Co.,Ltd.

Add: No 1201, Yinhai Building, Caoxi Road,
Xuhui District, Shanghai

24h Hotline: 15900706965

Website: www.pingyiao.com

Tel: (86) 021-64820099

Fax: (86) 021-64513829

E-mail: info@jichuan.sh.cn