



meguinfo

Art.-Nr. 3215.000

Stand: 94.12

megol Getriebefließfett GP1H-25

A sodium soap liquid gear grease, produced from carefully selected base materials and special additives. It contains wear-reducing additives and excels through good corrosion protection ability. For use in closed gears which require grease lubrication.

Service range from -25 °C to +100 °C.
Brief temperature-peaks up to +120 °C are permissible.

Identification acc.to DIN 51502: GP1H-25

Lubrication : lubrication grease DIN 51826 GP1H-25

Characteristic data

approx. values

Appearance and properties

natural colour, half-flowing, long-

Saponification type

drawing

Na

base oil viscosity at 40 °C	DIN 51562	mm ²	220
Flash point	DIN ISO 2592	°C	240
Pour point	DIN ISO 3016	°C	- 20
Drip point	DIN ISO 2176	°C	150
Consistency class	DIN 51818		1
Fulling penetration	DIN ISO 2137	0,1 mm	320-340
Fulling stability	DIN ISO 2137		
Difference after 5.000 u. 60 DH		0,1 mm	< 30
Difference after 100.000 u. 60 DH		0,1 mm	< 40
Anti-corrosion properties			
Emcor-method	DIN 51802	Corr.-degr.	0
Copper strip test	DIN 51811	Corr.-degr.	1-100
solid foreign bodies			
Test screen mesh 140 µ	DIN 51813	mg / kg	< 4
Water content	DIN ISO 3733	g / 100 g	< 0,1
Ashes, oxide	DIN EN 7	g / 100 g	1,4

Shanghai Jichuan Trading Co.,Ltd.

Add: No 1201, Yin Hai Building, Caoxi Road,
Xuhui District, Shanghai

24h Hotline: 15900706965

Website: www.pingyiao.com

Tel: (86) 021-64820099

Fax: (86) 021-64513829

E-mail: info@jichuan.sh.cn



Shanghai Jichuan Trading

VKA welding power	DIN 51350 T4	N	3000/3200
FZG- gear test , short Normal test A/2,8/90	DIN 51354 failure load level Special weight change	mg/KWh	12 < 0,27

Shanghai Jichuan Trading Co., Ltd.

Shanghai Jichuan Trading Co.,Ltd.

Add: No 1201, Yin Hai Building, Caoxi Road,
Xuhui District, Shanghai

24h Hotline: 15900706965

Website: www.pingyiao.com

Tel: (86) 021-64820099

Fax: (86) 021-64513829

E-mail: info@jichuan.sh.cn