



Assembly Paste 48

DESCRIPTION Assembly Paste 48 is used for basic and maintenance lubrication for assembly and repair work in all areas. Ideal for running in sliding surfaces and plain bearings. This paste consists of a select combination of solid lubricants. Wear can be significantly reduced using Assembly Paste 48.

PROPERTIES

- Good adhesion properties
- Optimum wear protection
- Outstanding emergency operation lubrication
- Good corrosion protection
- Minimum friction

TECHNICAL DATA

Color	: gray-black
Base	: Mineral oil
Additives (solid lubricant)	: MoS ₂ 33 %, graphite 6 %
Density at 20 °C	: 1.3 g/cm ³
Press-Fit Test, kinetic friction	: 0.12 μ
Thread friction	: 0.09 μ
Operating temperature range	: -35 °C to 450 °C

AREAS OF APPLICATION For basic and maintenance lubrication in all technical areas.

APPLICATION Depending on the existing conditions, Assembly Paste 48 may be applied to the clean sliding surfaces using a paint brush, brush or lint-free cloth. Can be applied in excess.

AVAILABLE PACK SIZES

LM 48 Assembly Paste	1 kg	Part no. 9031
----------------------	------	---------------

Shanghai Jichuan Trading Co.,Ltd.

Add: No 1201, Yin Hai Building, Caoxi Road,
Xuhui District, Shanghai

24h Hotline: 15900706965

Website: www.pingyiao.com

Tel: (86) 021-64820099

Fax: (86) 021-64513829

E-mail: info@jichuan.sh.cn



Shanghai Jichuan Trading

Shanghai Jichuan Trading Co., Ltd.

Shanghai Jichuan Trading Co.,Ltd.

Add: No 1201, Yin Hai Building, Caoxi Road,
Xuhui District, Shanghai

24h Hotline: 15900706965

Website: www.pingyiao.com

Tel: (86) 021-64820099

Fax: (86) 021-64513829

E-mail: info@jichuan.sh.cn