



Art.-Nr.: 2405.000

Stand: 96.04

## megol Haftoel CGL 220

Lubricants with a specially added adhesive and wear-inhibiting additives. Used for continuous loss process when normal lubricating oils are thrown off by vibration or rotation such as motor saw chains, saw frames and the like.

### Characteristic data

### Approx. values

ISO viscosity class	DIN 51519		VG 220
Viskosity at 40°C	DIN 51562	mm <sup>2</sup> /s	220
Viskosity at 100°C	DIN 51562	mm <sup>2</sup> /s	18,5
Viscosity index	DIN ISO 2909		90
Colour pursuant to ASTM	DIN 51578		3
Density at 15°C	DIN 51757	kg/m <sup>3</sup>	900
Flash point	DIN ISO 2592	°C	250
Pourpoint	DIN ISO 3016	°C	-15
Ash, oxide	DIN EN 7	g/100 g	< 1

Shanghai Jichuan Trading Co.,Ltd.

Add: No 1201, Yin Hai Building, Caoxi Road,  
Xuhui District, Shanghai

24h Hotline: 15900706965

Website: [www.pingyiao.com](http://www.pingyiao.com)

Tel: (86) 021-64820099

Fax: (86) 021-64513829

E-mail: [info@jichuan.sh.cn](mailto:info@jichuan.sh.cn)