



meguinfo

Artikel Nr.: 2411.000

Stand: 95.04

megol Schaloel Spezial FS 7

High efficient, not emulsifying forming oil for the undeluted service of metal and woodformwork at the concrete industrie and prestressed concrete manufacturing. The oil have to be painted on the survice. The formwork could be applied with the oil several days before or immediately before the betonpouring process. Very easy and clean deforming is garantied. Good hardening, smooth surfaces with exact profilet edges at economicalst application.

tech. data			approx. values
Viscosity at 40 °C	DIN 5156	2mm ² /s	8,0
ASTM colour	DIN 51578		0,5
Density at 15 °C	DIN 51757	kg/m ³	860
Flash point	DIN ISO 2592	°C	120
Pour point	DIN ISO 3016	°C	< - 40
Suphate, ash	DIN EN 7	g/100g	< 0,01
Content of non dissolved substances	DIN 51592	g/100 g	m.n.n. *)
Watercontent	DIN ISO 3733	g/100 g	m.n.n. *)
Neutralization index, acid	DIN 51558 Teil 1	mg KOH/g	86.9
Saponification index	DIN 51559	mgKOH/g	7.0

Shanghai Jichuan Trading Co.,Ltd.

Add: No 1201, Yin Hai Building, Caoxi Road,
Xuhui District, Shanghai

24h Hotline: 15900706965

Website: www.pingyiao.com

Tel: (86) 021-64820099

Fax: (86) 021-64513829

E-mail: info@jichuan.sh.cn